

Template Issues and Proposed Resolutions

Revision 9

John H. Spicer
Edison Design Group, Inc.
jhs@edg.com

November 5, 1994

Revision History

Version 1 – March 5, 1993: Distributed in Portland and in the post-Portland mailing.

Version 2 – May 28, 1993: Distributed in pre-Munich mailing. Reflects tentative decisions made in Portland and additional issues added after the Portland meeting. In Portland, the extensions working group reviewed most of the issues from 1.1 to 2.8 and also reviewed 6.3.

Version 3 – September 28, 1993: Distributed in pre-San Jose mailing. Reflects decisions made in Munich. No new issues were added in this revision.

Version 4 – November 24, 1993: Distributed in post-San Jose mailing. Reflects decisions made in San Jose. Note that issues that have been closed as a result of formal motions in San Jose will be omitted from subsequent versions of this paper. In San Jose the extensions working group identified a number of issues that required additional work. These issues have not been addressed in this paper but will be addressed in the next revision.

Version 5 – January 25, 1994: Distributed in the Pre-San Diego mailing. The 41 closed issues have been removed, 20 have been added, and a few existing ones have been updated.

Version 6 – March 25, 1994: Distributed in the Post-San Diego mailing. Reflects decisions made in San Diego. Note that issues that have been closed as a result of formal motions in San Diego will be omitted from subsequent versions of this paper. In San Diego the extensions working group identified a number of issues that required additional work. These issues have not been addressed in this paper but will be addressed in the next revision.

Version 7 – June 1, 1994: Distributed in the Pre-Waterloo mailing. The 24 issues closed in version 6 have been removed and 16 new issues have been added.

Version 8 – November 3, 1994: Distributed in Valley Forge and in the post-Valley Forge mailing. Reflects decisions made in Waterloo. This version contains only issues closed in Waterloo. Version 9 will be distributed at the same time as version 8 and will contain the open issues and new issues.

Version 9 – November 5, 1994: Distributed in Valley Forge and in the post-Valley Forge mailing. Issues closed in version 8 have been removed and new issues have been added.

Introduction

This document attempts to clarify a number of template issues that are currently either undefined or incompletely specified. In general, this document addresses smaller issues.

Of the issues that are addressed, some are covered in far more detail than others. Some of the resolutions represent solid proposals while others are more like trial balloons. The more tentative proposals are so designated in the body of the document.

Even those resolutions that represent fairly solid proposals are *only* proposals. This document is not intended as a formal proposal of any specific language changes. Rather, it is intended as to be used as a framework for discussion of these issues. Hopefully this will ultimately result in formal proposals for language changes.

Organization of the Document

The document is organized in sections. Each section consists of a list of questions. Each question has an answer, a status, the version number of the first version of this document that included the question, and the version number of the last change in the question. This allows the reader to skip over questions that have not changed since the last time he or she read the document.

Acknowledgements

I would like to thank Bjarne Stroustrup who contributed greatly by providing issues, reviewing and improving upon proposed resolutions, and providing insights into other language changes that may impact templates.

Summary of Issues

Because this is a rather long document this summary is provided to allow the reader to quickly find issues in which he or she may be interested. Note that closed issues have been removed from the body of the paper. Please refer to a previous version of the paper for additional information on these issues.

Template Parameters

- 1.1 Can template parameters have default arguments? (closed in version 4)
- 1.2 Where can default arguments for template parameters be specified? (closed in version 4)
- 1.3 Can a type parameter be used in the type declaration of a nontype parameter? (closed in version 4)
- 1.4 Can a nontype parameter as used above have a default argument? (closed in version 4)
- 1.5 Should it be possible to redeclare a template parameter name to mean something else inside a template definition? (closed in version 4)
- 1.6 Can the name of a nontype parameter be omitted? (closed in version 4)

- 1.7 Can the name of a type parameter be omitted? (closed in version 4)
- 1.8 Can a typedef appear in a template declaration? (closed in version 4)
- 1.9 Can a nontype parameter have a reference type? (closed in version 4)
- 1.10 Are qualifiers allowed on nontype parameters? (closed in version 4)
- 1.11 May a template parameter have the same name as the class template with which it is associated? (closed in version 4)

Class Template References

- 2.1 Can a nontype parameter that is not a reference be used as an lvalue or have its address taken? (closed in version 4)
- 2.2 Can the class template name be used as a synonym for the current instantiation inside a class template? (closed in version 4)
- 2.3 Can a class template have a template parameter as a base class? (closed in version 4)
- 2.4 Can a local type be used as a type argument of a class template? (closed in version 4)
- 2.5 Can a character string be a nontype argument? (closed in version 4)
- 2.6 Can any conversions be done on nontype actual arguments of class templates? (closed in version 6)
- 2.7 What causes a template class to be instantiated? (closed in version 4)
- 2.8 How can a class template name be used within the definition of the template? (closed in version 6)
- 2.9 The previous rule makes possible runaway recursive instantiations. How should an implementation prevent this? (closed in version 5)
- 2.10 At what point are names injected? (closed in version 6)
- 2.11 Does an array parameter decay to a pointer type? (closed in version 6)
- 2.12 What can be used as an actual argument for a parameter that is a reference? (closed in version 4)
- 2.13 Can template parameters be used in elaborated type specifiers? (closed in version 4)
- 2.14 Can a class template or function template be declared as a friend of a class? (closed in version 6)
- 2.15 Can template arguments be supplied in explicit destructor calls? (closed in version 4)

- 2.16 What happens if the same name is used for a template parameter of an out-of-class definition of a member of a class template and a member of the class? (closed in version 6)
- 2.17 What happens if the name of a template parameter of a class template is also the name of a member of one of its base classes? (closed in version 6)
- 2.18 When must a type used within a template be completed? (closed in version 6)
- 2.19 Must a specialization declaration precede the use of a class template in a context that requires only an incomplete type? (closed in version 6)
- 2.20 Proposal to defer error checking for `operator ->`. (closed in version 6)
- 2.21 When are names considered known in a template dependent base class? (closed in version 6)
- 2.22 Proposed revision to rules for explicit instantiation of all class members. (closed in version 8)
- 2.23 How does name injection interact with the semantics of friend declarations?

Function Templates

- 3.1 Can function templates have default function parameters? (closed in version 4)
- 3.2 Can the parameters with default arguments involve template parameters in their types? (closed in version 5)
- 3.3 Can a local type be used as a type argument of a template function? (closed in version 4)
- 3.4 Can any conversions be done when matching arguments to function templates? (closed in version 5)
- 3.5 The WP requires that every template parameter be used in an argument type of a function template. What constitutes a “use” of a template parameter in an argument type? (closed in version 4)
- 3.6 Can unnamed types be used as template arguments? (closed in version 4)
- 3.7 Can template parameters be used in qualified names in function template declarations?
- 3.8 Can a noninline function template be instantiated when referenced? (closed in version 4)
- 3.9 A proposal to allow conversions in function template calls. (closed in version 6)
- 3.10 What happens when the explicit specification of function template arguments results in an invalid type? (closed in version 6)

- 3.11 How do default arguments work when using new explicit specialization declarations? (closed in version 6)
- 3.12 How do old style specialization declarations interact with new style ones? (closed in version 6)
- 3.13 Revisiting default arguments.
- 3.14 What are the rules regarding use of the inline keyword in function template declarations?
- 3.15 How may elaborated type specifiers be used in function template declarations? (closed in version 8)
- 3.16 Clarification of template parameter deduction rules. (closed in version 8)
- 3.17 How may an overloaded function name be used as a function template argument in a context that requires parameter deduction? (closed in version 8)
- 3.18 Must a function template declaration be visible when an instance of the template is called? (closed in version 8) item[3.19] What are the rules regarding the deduction of template template parameters? (closed in version 8)
- 3.20 How are type/expression ambiguities resolved in explicitly qualified function template calls?

Member Function Templates

- 4.1 Are inline member functions that are not used by a given class template instance instantiated? (closed in version 4)
- 4.2 Can a noninline member function or a static data member be instantiated when referenced? (closed in version 4)
- 4.3 Must the template parameter names in a member function definition match the names used in the class definition? (closed in version 4)
- 4.4 What are the rules regarding use of the inline keyword in member function declarations? (closed in version 6)
- 4.5 How are default arguments for parameters of member functions of class templates handled? (closed in version 4)
- 4.6 Can a class template member function be redeclared outside of the class? (closed in version 6)
- 4.7 Can a member function of a class specialization be instantiated from a member function of the class template? (closed in version 8)
- 4.8 Can a template member function be declared in a specialization declaration? (closed in version 8)
- 4.9 Can a member function defined in a class template definition be specialized? (closed in version 8)

Class Template Specific Declarations and Definitions

- 5.1 Can you create a specific definition of a class template for which only a declaration has been seen? (closed in version 4)
- 5.2 Can you declare an incompletely defined object type that is a specific definition of a class template? (closed in version 4)
- 5.3 Can the class template name be used as a synonym for the current specific definition inside the specific definition? (closed in version 4)
- 5.4 Can a specific definition of a class template be a local class? (closed in version 4)

Other Issues

- 6.1 Should classes used as template arguments have external linkage? (closed in version 4)
- 6.2 When must errors in template definitions be issued and when must they not be issued? (closed in version 4)
- 6.3 What kinds of types may be used in a function template declaration while still being able to deduce the template argument types? (closed in version 4)
- 6.4 Can a static data member of a class template be declared with an incomplete array type? (closed in version 4)
- 6.5 How should template arguments that contain ">" be parsed? (closed in version 4)
- 6.6 Can template versions of `operator new` and `operator delete` be declared? (closed in version 4)
- 6.7 How can a name that is undefined at the point of its use in a template declaration be determined to be a type or nontype? (closed in version 4)
- 6.8 May template declarations be given a linkage specification other than C++. (closed in version 6)
- 6.9 Should there be a translation limit that specifies a minimum depth of recursive instantiation that must be supported? (closed in version 6)
- 6.10 Can a single template declaration declare more than one thing? (closed in version 6)
- 6.11 Can a storage class be specified in a template parameter declaration? (closed in version 6)
- 6.12 Can an incomplete type be used as a template argument? (closed in version 6)
- 6.13 Can a template nontype parameter have a void type? (closed in version 6)
- 6.14 Can a nontype parameter be a floating point type? (closed in version 6)

- 6.15 What kind of expressions may be used as nontype template arguments?
- 6.16 Can a template parameter be used in an explicit destructor call? (closed in version 6)
- 6.17 Can pointer to member types be used as nontype parameters? (closed in version 8)
- 6.18 Issues regarding declarations of specializations.
- 6.19 Clarification of explicit designation of a name as a type. (closed in version 8)
- 6.20 Template compilation model proposal. (withdrawn - last in version 7)
- 6.21 How is a dependent name known to be a template?
- 6.22 Interaction of templates and namespaces.
- 6.23 Floating point template parameters revisited.
- 6.24 May function types be used as template parameters?
- 6.25 WP clarification: overloaded functions as template arguments
- 6.26 WP clarification: access checking an template arguments

Nontype Parameters for Function Templates

A proposal for nontype parameters for function templates as required by the `Bitset` class. (closed in version 4)

Class Template References

2.23 Question: How does name injection interact with the semantics of friend declarations?

The semantics of friend declarations in class templates are not clear. Prior to adoption of the “no injection” rule, most implementations seem to treat a function declared in a friend declaration in a manner similar to the equivalent declaration appearing outside of the template. The declaration, in addition to granting friendship, also affected overload resolution. In the following example `f(A<int>,int)` is injected from the instantiation of `A<int>`. As a result, the call of `f(ai, 'c')` is treated differently than the call of `f(1, 'c')` because the former allows conversions of its arguments while the latter does not¹.

```
template <class T> void f(T, int);

template <class T> struct A {
    friend void f(A<T>, int);
};
```

¹This example is written using the “old” rules that permitted name injection and also the rules that prohibited conversion of function template arguments. Under the new conversion rules, the conversion of `char` to `int` would be allowed even for the function template call.

```

int main()
{
    A<int> ai;
    f(ai, 'c'); // Calls f(A<int>,int) with conversion
    f(ai, 1);  // Calls f(A<int>,int)
    f(1, 'c'); // Error - no matching function
    f(1, 1);   // Calls f(int,int)
}

```

The motivation for the “no injection” rule was to avoid the silent introduction of declarations that affect overload resolution, so clearly the old semantics of friend declarations are made obsolete by the no injection rule. But what are the new semantics?

Proposal one: A friend declaration in a template class conveys friendship, but does nothing more. It has no effect on overload resolution or on the source of the definition. A specialization declaration may not be used in a friend declaration. A class specialization is treated as a normal class declaration for purposes of injection.

This proposal has a number of unfortunate consequences. A friend declaration in a class template is unlike any other declaration in the language. Furthermore, when selecting rules for class specializations one must choose between the normal class rules and the class template rules. Either choice results in some kind of inconsistency. Either it is impossible to write a class specialization whose semantics duplicate those of the class template or it is impossible to write a class specialization (or class template) whose semantics duplicate those of a normal class.

```

template <class T> void f(T, int);

struct A {
    friend void f(A, int); // Friendship & overload resolution
    friend void f<>(A int); // ???
};
template <class T> struct B {
    friend void f(B<T>, int); // Friendship only
    friend void f<>(B<T>, int); // ???
};
void f(B<int>, int); // Affects only overload resolution
void f<>(B<char>, int); // Affects only source of definition

```

Proposal two: Proposal two is a proposal to bring back name injection. John Barton and Lee Nackman of IBM have a paper in the pre-Waterloo mailing arguing that injection from templates is an important facility. As a consequence of the Barton/Nackman paper the injection issue may be revisited. Should the committee’s previous decision regarding injection be reversed I want to have an equivalent clarification of friend semantics available as part of such a resolution.

The first part of this proposal is a description of the proposed name injection rules (this was the original version of issue 2.10 from revision 1 through revision 4 of this paper).

```

// Name injection
template <class T> struct A {

```



```

        friend void f(A<T>){}
        friend void f2(struct X* x);
};

void main()
{
    void* fp;
    X* x;    // Error - X is undefined
    fp = f; // Error - f is undefined
    f2(x);  // Error - f2 is undefined
    A<int> a;
    X* x2;  // OK - X defined during instantiation of A<int>
    fp = f; // OK - only one instance of f
    A<char> ac;
    fp = f; // Error - f is now overloaded
}

```

Nothing is injected when the class template is scanned. `X`, `f(A<int>)`, and `f2` are injected into the global scope when `A<int>` is instantiated. When `A<char>` is instantiated, `f(A<char>)` is injected into the global scope. `X` already exists so nothing else is done with `X`.

The second part of the proposal clarifies the semantics of friend declaration in template classes.

A friend declaration in a template class, as in other classes, conveys friendship and injects a declaration into the enclosing scope that affects overload resolution. A specialization declaration may not appear in a friend declaration.

The advantage of this proposal is that normal classes, class templates, and class specializations are all handled in the same way.

Status: Open

Version added: 7

Version updated: 7

Function Templates

- 3.7 Question: Can template parameters be used in qualified names in function template declarations?

```

template <class T> struct A {
    struct B {
        friend B& operator +(const B&, const B&);
    };
};

template <class T> A<T>::B& operator +
    (const A<T>::B& b1, const A<T>::B& b2){}

```

```

template <class T> void f(A<T>, A<T>::B){}

int main()
{
    A<int>          a;
    A<int>::B      b1;
    A<int>::B      b2;
    A<int>::B      b3;
    f(a, b1);
    b1 = b2 + b3;
}

```

There are two issues involved here

1. how does one specify that a name like `A<T>::B` is a type?
2. can `T` in `A<T>::B` be deduced?

The first issue is discussed, and a proposal made in 94-0191/N0578 “Major Template Issues, Revision 0”, and will not be discussed here.

The remainder of this discussion focuses on the type deduction issue. This deduction has deadlocked in the past, partially on the lack of substantial justification for this feature.

I have discussed this issue with Alex Stepanov who informed me that not only it is important for STL, but the current implementation of STL has had to use member functions where friend operator functions are really needed, because the compiler being used to develop STL does not support this feature.

The question really boils down to “can nested types be used in function template declarations”. The arguments for supporting this kind of usage are the same as the arguments for providing nested types at all. In my opinion, it should be possible to take just about any class and convert it into a template. Banning nested types in function template declarations would make it impossible to convert many kinds of classes into template equivalents.

There are at least two compilers (IBM and EDG) that currently support this feature.

Note that now that nontype template parameters may be used in function templates, the same principle applies to nontype parameters. For example,

```

template <int I> struct A {
    struct B {};
};

template <int I> void f(A<I>, A<I>::B){}

```

One concern that has been expressed regarding this feature is that in a construct such as `T::A`, `T` is the class in which `A` is declared and not strictly a type attribute of `A`. While this is true, it does not change the fact that what is being deduced is in fact a type (or nontype in the case of nontype parameters). The question is whether the class of which a type is a member can be used as information from which type (or nontype) information is deduced.

In other words, we are not adding a new kind of deduction, we are simply expanding the kind of information that can be used by the deduction process.

Answer: Yes, this kind of deduction is allowed.

Note that the type of the actual argument must be a nested type (class/struct, union, or enum). A typedef is simply a synonym for another type and cannot be used.

This proposed resolution suggests that a compiler should be able to determine that names used in this context are types. An alternative would be to require explicit designation as a type. The current facility for such designation (using `typedef`) is not well suited for this kind of construct, so some change to the current facility would probably be required.

```
template <class T> struct A {
    typedef T::X;
    T::X x;
    T::X f();
    friend void g(T::X);
    friend void g(T::X2); // Error
    template <class U> void h(U::Y); // OK
};

template <class T> T::X A<T>::f(){} // OK
template <class T> void g(T::X); // OK
```

Status: Open

Version added: 1

Version updated: 7

3.13 Revisiting default arguments.

I would like to recommend that we revisit the proposed rules for default arguments to specify that the default arguments for a given specialization be locked in at the point that name binding occurs.

This is motivated by examples such as the following. If it is possible to add default arguments to a function template with template parameters that depend on other template parameters, then the new default argument would need to be type-checked for each of the instantiations that have already been generated – a process which has the potential of yielding new errors for the already generated instantiations.

While this is possible to do, I think it would be more confusing to users than simply saying that the default argument information is locked in when the first instance of the template is referenced. I would recommend the same for member functions.

```
template <class T> void f(T, T, T*);

void g1()
{
    int i;
    f(i,i,&i); // Default arg information locked here
}
```

```

template <class T>
void f(T, T, T* = new T); // Error - default arguments modified
                          // after the first use

void g2()
{
    int i;
    f(i,i); // Without this rule, is this legal?
    char c;
    f(c,c); // How about this?
}

```

In the following example, a default argument is provided that is only valid for certain instantiations. How would the behavior of this program change if the default argument declaration (currently declared at point #2) were moved to either #1 or #3?

If the declaration were at point #1, an error would be issued at the call labeled #4 because the default argument is incompatible with the parameter type.

If the declaration were at point #2, should an error be issued at point #2 because the default argument is invalid for an existing instantiation? Or, should the error only be issued if the default argument value is actually used in an invalid call?

Unless we adopt a rule that prohibits changing the default arguments once name binding has occurred, we introduce a situation in which the legality of one call depends on whether or not a previous call of the same function has been seen. I think this is undesirable.

```

template <class T> void f(T, T);
struct A {};
// template <class T> void f(T, T = 1); // #1

void g1()
{
    int i;
    A a;
    f(i,i);
    f(a,a); // #4
}

template <class T> void f(T, T = 1); // #2

void g2()
{
    int i;
    A a;
    f(i);
    f(a,a); // Is this an error?
    f(a); // Error: default argument has wrong type
}

```

```
// template <class T> void f(T, T = 1); // #3
```

Status: Open

Version added: 5

Version updated: 7

- 3.14 Question: What are the rules regarding use of the inline keyword in function template declarations?

Answer: Whether a function template is declared as being inline or static has no effect on specializations. If a specialization is to be inline it must be declared inline regardless of how the template was declared.

```
template <class T> void f(T) {}
template <class T> inline void g(T) {}

inline void f<>(int){} // OK
void g<>(int){} // OK (not inline)
```

Declarations of any given template or specialization must be consistent with previous declarations (using the same rules that apply to nontemplate functions).

```
template <class T> void f(T) {} // Defaults to noninline
template <class T> inline void f(T); // Error: conflicts with
// previous declaration

template <class T> inline void g(T) {}
template <class T> void g(T); // OK - defaults to previous
// declaration
```

Status: Open

Version added: 7

Version updated: 7

- 3.20 Question: How are type/expression ambiguities resolved in explicitly qualified function template calls?

```
template <class T> void f(){}
template <int I> void f(){}

int main()
{
    f<int>>(); // which f?
}
```

Answer: As with other cases in the language, the ambiguity between a type-id and an expression is resolved as a type-id.

Status: Open

Version added: 9

Version updated: 9

Other Issues

6.18 Issues regarding declarations of specializations.

The language was recently revised to require that a specialization be declared before it is used. For example,

```
template <class T> void f(T){}
void f<>(int); // Declares that a specialization of
              // f(int) will be provided
```

While this usage is clear for normal template functions, it is problematic for members of template classes. In the nonmember case shown above, the template argument list makes it clear that the function is a specialization. In the member function, only the argument list of the class is present, making the purpose of the declaration less clear. For static data members the problem is even worse because the syntax for the specialization is already used to mean a definition for which no specific value is provided.

```
template <class T> struct A {
    void f();
    static int i;
};

void A<int>::f(); // Is this a specialization declaration?
int A<int>::i;   // This is a definition, not a declaration
```

I propose that a keyword be added to designate a declaration as a specialization and that the current syntax for specializations be eliminated. The following are some of the possible keywords:

```
template <class T> struct A {
    static int i;
};

specialize int A<int>::i;
specialise int A<int>::i;
specific int A<int>::i;
specialism int A<int>::i; // Yes, specialism is a real word
```

Of these, I personally prefer **specialize** because it matches the wording used in the working paper. If **specialize** is not acceptable because it is spelled differently in some countries, then **specific** would probably be my second choice.

Status: Open

Version added: 7

Version updated: 7

6.21 Question: How is a dependent name known to be a template?

This issue was raised by Erwin Unruh in `c++std-ext-2239`.

In the following example from Erwin's posting, the `f` on the indicated line refers to an integer data member in `A`, and to a function template in `A<C>`.

```

template <class T> class A : public T {
    void foo(){
        T t;
        f < 1 > (t,t);        // critical line
    }
};

class B {
    int f;
};
int operator> (B, bool);
A<B> ab;

class C {};
template <int I, class T> void f(T, C);
A<C> ac;

```

In another example from Erwin's posting, a variation of the problem using member templates is illustrated.

```

struct A { int x; };
struct B { template<int> void x(int); };

template <class T> struct C : public T {
    void foo(){
        x < 1 > (2);        // critical line #1
    }
};

C<A> ca;        // #1 is double comparison
C<B> cb;        // #1 is template function

```

Answer: We currently have a means of designating that a given name is a type for use when a type will be defined in a template dependent base class. I propose a similar mechanism for templates. A name will be assumed not to be a template unless explicitly designated as one.

```

template <class T> class A : public T {
    template f; // May be placed here
    void foo(){
        T t;
        template f; // or may be placed here
        f < 1 > (t,t);
    }
};

```

The second example would be modified as follows:

```

struct A { int x; };
struct B { template<int> void x(int); };

```

```

template <class T> struct C : public T {
    template T::X; // May be placed here
    void foo(){
        template T::X; // or may be placed here
        x < 1 > (2); // critical line #1
    }
};

C<A> ca; // #1 is double comparison (now made invalid)
C<B> cb; // #1 is template function

```

The identifier following the `template` keyword must either have no qualifier or have a qualifier that begins with either a template parameter or a template class name.

If this proposal is adopted, I believe we should modify one of the existing uses of the keyword `template`. It is currently used for template declarations and for explicit instantiation requests. I believe that using it for both explicit instantiation requests and for explicit template designation would be confusing. I propose that a new keyword `instantiate` be added for use in explicit instantiation requests and that the keyword `template` no longer be supported in that context.

Status: Open

Version added: 7

Version updated: 7

6.22 Interaction between templates and namespaces

The September 20, 1994 Working Paper contains a new section (with an editorial box) that specifies that an instantiation caused by a template reference within a namespace is done within the namespace that contains the reference. Prior to this change the WP specified that the instantiation was done at the global scope.

The new WP description does not address what happens if the template itself was defined in a namespace.

```

namespace N {
    void g(int);
    template <class T> void h(T);
    void i(int);
    template <class T> void f(T t)
    {
        g(t);
        h(t);
    }
};

namespace X {
    void g(int);
    void h(int);
};

```


Answer: For consistency, floating point template parameters should be allowed unless there is a compelling reason not to do so. There are compilers that support them now (Microsoft and EDG, possibly others).

One unusual property of floating point numbers is the fact that it is difficult to know whether, on a given implementation, two floating point expressions will evaluate to *exactly* the same value. Consequently, it is impossible to know whether, on a given implementation, `a_one_third` and `another_third` have the same type. This should not come as a surprise to anyone familiar with the use of floating point numbers, however.

Status: Open

Version added: 9

Version updated: 9

6.24 Question: May function types be used as template parameters?

The use of function types as template parameters is problematic. It can result in something that looks like an object changing into a function declaration. Note that it is not possible to define a member such that it could be instantiated as either an object or a function.

```
template <class T> struct A {
    static T t;
};
```

```
A<int()> a1; // Oops! A<int()>::t is now a function!
```

Likewise, a function type inherited from a template dependent base class can create the same problem.

```
template <class X> struct A : public X {
    typename X::T;
    static X::T t;
};
```

```
struct B {
    typedef int(T)();
};
```

```
A<B> a1; // Oops! A<B>::t is now a function!
```

Answer: A function type may not be used as a template parameter. A type named in a `typename` directive may not refer to a function type.

Status: Open

Version added: 9

Version updated: 9

6.25 WP clarification: overloaded functions as template arguments

Section 14.7 says that overloaded functions may not be used as template arguments. This is an unnecessary restriction and a change that was never voted on.

Because there are no conversions allowed on function pointers, and because the type of the template parameter is known, there is no problem in selecting a member from a set of overloaded functions as illustrated in the following example.

```

void f(int);
void f(char);

template <void (*fp)(int)> struct A {};

A<&f> af; // Should be OK

```

Status: Open

Version added: 9

Version updated: 9

6.26 WP clarification: access checking an template arguments

Section 14.7 describes access checking with respect to template arguments, and says, in effect, that the access checking of a template argument depends on how it is used within the template.

Accessibility of a type used as a template argument should be done the same way as all other access checking. Specifically, it should be done where the name is referenced (i.e., when scanning the template arguments), not inside the instantiation of the template. The reference of `Y::S` should be illegal even if the template never used the parameter `T`. Access checking of names like `T::Z`, of course, needs to be done within the template.

Another way of saying this is that the validity of an instantiation (as far as access checking is concerned) should not depend on which point of instantiation is used.

```

template <class T> struct X {
    T t;
};

class Y {
private:
    struct S {};
    X<S> xs; // OK
};

X<Y::S> xs2; // Error - S is not accessible

```

Status: Open

Version added: 9

Version updated: 9