Template for comments and secretariat observations

Date:	Document:
-------	-----------

1	2	(3)	4	5	(6)	(7)
MB	Clause No./ Subclause No./ Annex (e.g. 3.1)	Paragraph/ Figure/Table/ Note (e.g. Table 1)	Type of com ₂ ment	Comment (justification for change) by the MB	Proposed change by the MB	Secretariat observations on each comment submitted
CA	5.2.2.1	5	ed	"Because this feature is only useful when the stream is opened for reading or updating" says that the feature is useful for reading. Given the buffer contents are not defined at that point, we need an example where reading would be useful (Ex. A bad random number generator seed).	"Because this feature is only useful when the stream is opened for updating"	Agreed, change should be made.
CA	5.2.2.1	5	ed	"fmemopen call may fail if the mode argument does not include a +" contradicts the reading aspect of the "Because this feature is only useful when the stream is opened for reading or updating" statement given "+" means update.	Same as above.	See above.
CA	5.2.3.{1,2} 5.4.2.{1,2}		ed	Handling the dynamically allocated memory is explicitly mentioned in most of the listed functions as follows: 5.2.2.1 p 5 – Automatically freed. 5.2.2.2 p 3 – User must call free. 5.2.3.3 p 3 – User must call free. 5.2.4.1 – Pointer can be passed to free The 5.2.3.1 and 5.2.3.2 functions do not mention the way that the memory should be freed.	Added to 5.2.3.1, 5.2.3.2, 5.4.2.1, 5.4.2.2: "The buffer should be freed by the caller by means of a call to free when the contents are no longer required."	Agree with the changes to 5.2.3.1 and 5.4.2.1. The change to 5.2.3.2 and 5.4.2.2 does not seem reasonable; the changes to 5.2.3.1 and 5.4.2.1 are referenced in 5.2.3.2 and 5.4.2.2.

¹ MB = Member body (enter the ISO 3166 two-letter country code, e.g. CN for China; comments from the ISO/CS editing unit are identified by **)

² **Type of comment: ge** = general **te** = technical **ed** = editorial