ISO/IEC JTC 1/SC 22/WG 14 N1781

Date: yyyy-mm-dd

Reference number of document: ISO/IEC TS 18661-2

Committee identification: ISO/IEC JTC 1/SC 22/WG 14

Secretariat: ANSI

Information Technology — Programming languages, their environments, and system software interfaces — Floating-point extensions for C — Part 2: Decimal floating-point arithmetic

10 Technologies de l'information — Langages de programmation, leurs environnements et interfaces du logiciel système — Extensions à virgule flottante pour C — Partie 2: décimal arithmétique flottante

Warning

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type: Technical Specification Document subtype: Document stage: (20) Preparation Document language: E

15

Copyright notice

This ISO document is a working draft or committee draft and is copyright-protected by ISO. While the reproduction of working drafts or committee drafts in any form for use by participants in the ISO standards development process is permitted without prior permission from ISO, neither this document nor any extract from it may be reproduced, stored or transmitted in any form for any other purpose without prior written permission from ISO.

Requests for permission to reproduce this document for the purpose of selling it should be addressed as shown below or to ISO's member body in the country of the requester:

ISO copyright office Case postale 56 CH-1211 Geneva 20 Tel. +41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

15 Reproduction for sales purposes may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

5

Contents

	Introduction Background	
	IEC 60559 floating-point standard	v
5	C support for IEC 60559	
	Purpose Additional background on decimal floating-point arithmetic	
	1 Scope	1
	2 Conformance	1
10	3 Normative references	1
	4 Terms and definitions	2
	5 C standard conformance	
	5.1 Freestanding implementations	2
45	5.2 Predefined macros	
15	5.3 Standard headers	
	6 Decimal floating types	8
	7 Characteristics of decimal floating types <float.h></float.h>	10
	8 Operation binding	15
	9 Conversions	15
20	9.1 Conversions between decimal floating and integer types	
	9.2 Conversions among decimal floating types, and between decimal floating and standard	
	floating types	
	 9.3 Conversions between decimal floating and complex types 9.4 Usual arithmetic conversions 	
25	9.5 Default argument promotion	
	10 Constants	
	11 Arithmetic operations	
	11.1 Operators	
	11.2 Functions	
30	11.3 Conversions	
	11.4 Expression transformations	20
	12 Library	
	12.1 Standard headers	
35	 12.2 Decimal floating-point environment in <fenv.h></fenv.h> 12.3 Decimal mathematics in <math.h></math.h> 	
30	12.3 Decimal mathematics in <math.h></math.h>	
	12.4.1 Quantum and quantum exponent functions	
	12.4.2 Decimal re-encoding functions	
	12.5 Formatted input/output specifiers	
40	12.6 strtod/ functions in <stdlib.h></stdlib.h>	
	<pre>12.7 wcstodN functions in <wchar.h></wchar.h></pre>	
	12.8 strfromd/v functions in <stdlib.h> 12.9 Type-generic math for decimal in <tgmath.h></tgmath.h></stdlib.h>	
45	Bibliography	50

Foreword

5

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TS 18661 was prepared by Technical Committee ISO JTC 1, *Information Technology*, Subcommittee SC 22, *Programming languages, their environments, and system software interfaces*.

ISO/IEC TS 18661 consists of the following parts, under the general title Floating-point extensions for C:

- Part 1: Binary floating-point arithmetic
- Part 2: Decimal floating-point arithmetic
- Part 3: Interchange and extended types
- 20 Part 4: Supplementary functions
 - Part 5: Supplementary attributes

Part 1 updates ISO/IEC 9899:2011 (Information technology — Programming languages, their environments and system software interfaces — Programming Language C), Annex F in particular, to support all required features of ISO/IEC/IEEE 60559:2011 (Information technology — Microprocessor Systems — Floating-point arithmetic).

25 a

Part 2 supersedes ISO/IEC TR 24732:2009 (Information technology – Programming languages, their environments and system software interfaces – Extension for the programming language C to support decimal floating-point arithmetic).

30

Parts 3-5 specify extensions to ISO/IEC 9899:2011 for features recommended in ISO/IEC/IEEE 60559:2011.

Introduction

Background

10

20

25

IEC 60559 floating-point standard

- The IEEE 754-1985 standard for binary floating-point arithmetic was motivated by an expanding diversity in floating-point data representation and arithmetic, which made writing robust programs, debugging, and moving programs between systems exceedingly difficult. Now the great majority of systems provide data formats and arithmetic operations according to this standard. The IEC 60559:1989 international standard was equivalent to the IEEE 754-1985 standard. Its stated goals were:
 - 1 Facilitate movement of existing programs from diverse computers to those that adhere to this standard.
 - 2 Enhance the capabilities and safety available to programmers who, though not expert in numerical methods, may well be attempting to produce numerically sophisticated programs. However, we recognize that utility and safety are sometimes antagonists.
- 3 Encourage experts to develop and distribute robust and efficient numerical programs that are 15 portable, by way of minor editing and recompilation, onto any computer that conforms to this standard and possesses adequate capacity. When restricted to a declared subset of the standard, these programs should produce identical results on all conforming systems.
 - 4 Provide direct support for
 - a. Execution-time diagnosis of anomalies
 - b. Smoother handling of exceptions
 - c. Interval arithmetic at a reasonable cost
 - 5 Provide for development of
 - a. Standard elementary functions such as exp and cos
 - b. Very high precision (multiword) arithmetic
 - c. Coupling of numerical and symbolic algebraic computation
 - 6 Enable rather than preclude further refinements and extensions.

To these ends, the standard specified a floating-point model comprising:

formats – for binary floating-point data, including representations for Not-a-Number (NaN) and signed infinities and zeros

30 *operations* – basic arithmetic operations (addition, multiplication, etc.) on the format data to compose a well-defined, closed arithmetic system; also specified conversions between floating-point formats and decimal character sequences, and a few auxiliary operations

context – status flags for detecting exceptional conditions (invalid operation, division by zero, overflow, underflow, and inexact) and controls for choosing different rounding methods

35 The IEC 60559:2011 international standard is equivalent to the IEEE 754-2008 standard for floating-point arithmetic, which is a major revision to IEEE 754-1985.

The revised standard specifies more formats, including decimal as well as binary. It adds a 128-bit binary format to its basic formats. It defines extended formats for all of its basic formats. It specifies data interchange

formats (which may or may not be arithmetic), including a 16-bit binary format and an unbounded tower of wider formats. To conform to the floating-point standard, an implementation must provide at least one of the basic formats, along with the required operations.

- The revised standard specifies more operations. New requirements include among others arithmetic operations that round their result to a narrower format than the operands (with just one rounding), more conversions with integer types, more classifications and comparisons, and more operations for managing flags and modes. New recommendations include an extensive set of mathematical functions and seven reduction functions for sums and scaled products.
- The revised standard places more emphasis on reproducible results, which is reflected in its standardization of more operations. For the most part, behaviors are completely specified. The standard requires conversions between floating-point formats and decimal character sequences to be correctly rounded for at least three more decimal digits than is required to distinguish all numbers in the widest supported binary format; it fully specifies conversions involving any number of decimal digits. It recommends that transcendental functions be correctly rounded.
- 15 The revised standard requires a way to specify a constant rounding direction for a static portion of code, with details left to programming language standards. This feature potentially allows rounding control without incurring the overhead of runtime access to a global (or thread) rounding mode.

Other features recommended by the revised standard include alternate methods for exception handling, controls for expression evaluation (allowing or disallowing various optimizations), support for fully reproducible results, and support for program debugging.

The revised standard, like its predecessor, defines its model of floating-point arithmetic in the abstract. It neither defines the way in which operations are expressed (which might vary depending on the computer language or other interface being used), nor does it define the concrete representation (specific layout in storage, or in a processor's register, for example) of data or context, except that it does define specific encodings that are to be used for data that may be exchanged between different implementations that conform to the specification.

IEC 60559 does not include bindings of its floating-point model for particular programming languages. However, the revised standard does include guidance for programming language standards, in recognition of the fact that features of the floating-point standard, even if well supported in the hardware, are not available to users unless the programming language provides a commensurate level of support. The implementation's combination of both hardware and software determines conformance to the floating-point standard.

C support for IEC 60559

20

25

30

The C standard specifies floating-point arithmetic using an abstract model. The representation of a floatingpoint number is specified in an abstract form where the constituent components (sign, exponent, significand) of the representation are defined but not the internals of these components. In particular, the exponent range, significand size, and the base (or radix) are implementation-defined. This allows flexibility for an implementation to take advantage of its underlying hardware architecture. Furthermore, certain behaviors of operations are also implementation-defined, for example in the area of handling of special numbers and in exceptions.

- 40 The reason for this approach is historical. At the time when C was first standardized, before the floating-point standard was established, there were various hardware implementations of floating-point arithmetic in common use. Specifying the exact details of a representation would have made most of the existing implementations at the time not conforming.
- Beginning with ISO/IEC 9899:1999 (C99), C has included an optional second level of specification for implementations supporting the floating-point standard. C99, in conditionally normative Annex F, introduced nearly complete support for the IEC 60559:1989 standard for binary floating-point arithmetic. Also, C99's informative Annex G offered a specification of complex arithmetic that is compatible with IEC 60559:1989.

ISO/IEC 9899:2011 (C11) includes refinements to the C99 floating-point specification, though is still based on IEC 60559:1989. C11 upgrades Annex G from "informative" to "conditionally normative".

ISO/IEC Technical Report 24732:2009 introduced partial C support for the decimal floating-point arithmetic in IEC 60559:2011. TR 24732, for which technical content was completed while IEEE 754-2008 was still in the later stages of development, specifies decimal types based on IEC 60559:2011 decimal formats, though it does not include all of the operations required by IEC 60559:2011.

Purpose

5

25

35

45

The purpose of this Technical Specification is to provide a C language binding for IEC 60559:2011, based on the C11 standard, that delivers the goals of IEC 60559 to users and is feasible to implement. It is organized into five Parts.

10

Part 1 provides changes to C11 that cover all the requirements, plus some basic recommendations, of IEC 60559:2011 for binary floating-point arithmetic. C implementations intending to support IEC 60559:2011 are expected to conform to conditionally normative Annex F as enhanced by the changes in Part 1.

Part 2, this document, enhances TR 24732 to cover all the requirements, plus some basic recommendations, 15 of IEC 60559:2011 for decimal floating-point arithmetic. C implementations intending to provide an extension for decimal floating-point arithmetic supporting IEC 60559:2011 are expected to conform to Part 2.

Part 3 (Interchange and extended types), Part 4 (Supplementary functions), and Part 5 (Supplementary attributes) cover recommended features of IEC 60559:2011. C implementations intending to provide extensions for these features are expected to conform to the corresponding Parts.

20 Additional background on decimal floating-point arithmetic

Most of today's general-purpose computing architectures provide binary floating-point arithmetic in hardware. Binary floating point is an efficient representation that minimizes memory use, and is simpler to implement than floating-point arithmetic using other bases. It has therefore become the norm for scientific computations, with almost all implementations following the IEEE 754 standard for binary floating-point arithmetic (and the equivalent international ISO/IEC 60559 standard).

However, human computation and communication of numeric values almost always uses decimal arithmetic and decimal notations. Laboratory notes, scientific papers, legal documents, business reports and financial statements all record numeric values in decimal form. When numeric data are given to a program or are displayed to a user, conversion between binary and decimal is required. There are inherent rounding errors involved in such conversions: decimal fractions cannot, in general, be represented exactly by binary floating-

30 point values. These errors often cause usability and efficiency problems, depending on the application.

These problems are minor when the application domain accepts, or requires results to have, associated error estimates (as is the case with scientific applications). However, in business and financial applications, computations are either required to be exact (with no rounding errors) unless explicitly rounded, or be supported by detailed analyses that are auditable to be correct. Such applications therefore have to take special care in handling any rounding errors introduced by the computations.

The most efficient way to avoid conversion error is to use decimal arithmetic. Currently, the IBM z/Architecture (and its predecessors since System/360) is a widely used system that supports built-in decimal arithmetic. Prior to the IBM System z10 processor, however, this provided integer arithmetic only, meaning that every number and computation has to have separate scale information preserved and computed in order to maintain 40 the required precision and value range. Such scaling is difficult to code and is error-prone; it affects execution time significantly, and the resulting program is often difficult to maintain and enhance.

Even though the hardware may not provide decimal arithmetic operations, the support can still be emulated by software. Programming languages used for business applications either have native decimal types (such as PL/I, COBOL, REXX, C#, or Visual Basic) or provide decimal arithmetic libraries (such as the BigDecimal class in Java). The arithmetic used in business applications, nowadays, is almost invariably decimal floatingpoint; the COBOL 2002 ISO standard, for example, requires that all standard decimal arithmetic calculations use 32-digit decimal floating-point.

The IEEE has recognized the importance of this. Decimal floating-point formats and arithmetic are major new features in the IEEE 754-2008 standard and its international equivalent IEC 60559:2011.

Information Technology — Programming languages, their environments, and system software interfaces — Floating-point extensions for C — Part 2: Decimal floating-point arithmetic

5 1 Scope

This document, Part 2 of ISO/IEC Technical Specification 18661, extends programming language C, as specified in IEC 9899:2011 (C11) with changes specified in Part 1 of ISO/IEC Technical Specification 18661, to support decimal floating-point arithmetic conforming to ISO/IEC/IEEE 60559:2011. It covers all requirements of IEC 60559 as they pertain to C decimal floating types.

10 This document supersedes ISO/IEC TR 24732:2009 (Information technology – Programming languages, their environments and system software interfaces – Extension for the programming language C to support decimal floating-point arithmetic).

This document does not cover binary floating-point arithmetic (which is covered in Part 1 of ISO/IEC TS 18661), nor does it cover most optional features of IEC 60559.

15 2 Conformance

An implementation conforms to Part 2 of Technical Specification 18661 if

- a) It meets the requirements for a conforming implementation of C11 with all the changes to C11 specified in Parts 1 and 2 of Technical Specification 18661; and
- 20 b) It defines <u>STDC_IEC_60559_DFP</u> to 201 ymmL.

NOTE Conformance to Part 2 of Technical Specification 18661 does not include all the requirements of Part 1. An implementation may conform to either or both of Parts 1 and 2.

3 Normative references

25 The following referenced documents are indispensable for the application of this document. Only the editions cited apply.

ISO/IEC 9899:2011, Information technology — Programming languages, their environments and system software interfaces — Programming Language C

ISO/IEC 9899:2011/Cor.1:2012, Technical Corrigendum 1

30 ISO/IEC/IEEE 60559:2011, Information technology — Microprocessor Systems — Floating-point arithmetic (with identical content to IEEE 754-2008, IEEE Standard for Floating-Point Arithmetic. The Institute of Electrical and Electronic Engineers, Inc., New York, 2008)

ISO/IEC TS 18661-1:yyyy, Information technology – Programming languages, their environments and system software interfaces – Floating-point extension for C – Part 1: Binary floating-point arithmetic

4 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 9899:2011 and ISO/IEC/IEEE 60559:2011 and the following apply.

4.1

5 **C11**

standard ISO/IEC 9899:2011, Information technology — Programming languages, their environments and system software interfaces — Programming Language C, including Technical Corrigendum 1 (ISO/IEC 9899:2011/Cor. 1:2012)

5 C standard conformance

10 **5.1 Freestanding implementations**

The following change to C11 + TS18661-1 expands the conformance requirements for freestanding implementations so that they might conform to this Part of Technical Specification 18661.

Change to C11 + TS18661-1:

Replace the fourth sentence of 4#6:

The strictly conforming programs that shall be accepted by a conforming freestanding implementation that defines __STDC_IEC_60559_BFP_ may also use features in the contents of the standard headers <fenv.h> and <math.h> and the numeric conversion functions (7.22.1) of the standard header <stdlib.h>.

with:

5.2 Predefined macros

²⁵ The following change to C11 + TS18661-1 replaces <u>______STDC__DEC_FP__</u>, the conformance macro for decimal floating-point arithmetic specified in TR 24732, with <u>______STDC__IEC__60559__DFP__</u>, for consistency with the conformance macro for Part 1 of Technical Specification 18661. Note that an implementation may continue to define <u>______STDC__DEC__FP__</u>, so that programs that use <u>______STDC__DEC__FP__</u> may remain valid under the changes in Part 2 of Technical Specification 18661.

30 Change to C11 + TS18661-1:

In 6.10.8.3#1, add:

- _____STDC_IEC_60559_DFP___ The integer constant 201ymmL, intended to indicate support of the decimal floating types and conformance with Annex F for IEC 60559 decimal floating-point arithmetic.
- 35 The following change to C11 + TS18661-1 specifies the applications of Annex F to binary and decimal floating-point arithmetic.

Change to C11 + TS18661-1:

Replace F.1#3:

[3] An implementation that defines <u>_____STDC_IEC_60559_BFP_</u> to 201ymmL shall conform to the specifications in this annex.356) Where a binding between the C language and IEC 60559 is indicated, the IEC 60559-specified behavior is adopted by reference, unless stated otherwise.

with:

5

15

25

30

[3] An implementation that defines <u>______STDC__IEC__60559_BFP__</u> to 201ymmL shall conform to the specifications in this annex for binary floating-point arithmetic.356)

[4] An implementation that defines <u>STDC_IEC_60559_DFP</u> to 201_{ymm}L shall conform to the specifications for decimal floating-point arithmetic in the following subclauses of this annex:

- F.2.1 Infinities and NaNs
- F.3 Operations
- F.4 Floating to integer conversions
- F.6 The return statement
- F.7 Contracted expressions
- F.8 Floating-point environment
- F.9 Optimization
- F.10 Mathematics <math.h>
- 20 For the purpose of specifying these conformance requirements, the macros, functions, and values mentioned in the subclauses listed above are understood to refer to the corresponding macros, functions, and values for decimal floating types. Likewise, the "rounding direction mode" is understood to refer to the rounding direction mode for decimal floating-point arithmetic.

[5] Where a binding between the C language and IEC 60559 is indicated, the IEC 60559-specified behavior is adopted by reference, unless stated otherwise.

5.3 Standard headers

The new identifiers added to C11 library headers by this Part of Technical Specification 18661 are defined or declared by their respective headers only if <u>STDC_WANT_IEC_60559_DFP_EXT</u> is defined as a macro at the point in the source file where the appropriate header is first included. The macro <u>STDC_WANT_IEC_60559_DFP_EXT</u> replaces the macro <u>STDC_WANT_DEC_FP</u> specified in TR 24732 for the same purpose. The following changes to C11 + TS18661-1 list these identifiers in each applicable library subclause.

Changes to C11 + TS18661-1:

In 5.2.4.2.1#1a, change:

to:

After 5.2.4.2.2#6a, insert the paragraph:

[6b] The following identifiers are defined only if <u>STDC_WANT_IEC_60559_DFP_EXT</u> is defined as a macro at the point in the source file where <float.h> is first included:

for *N* = 32, 64, and 128:

5

10

decN_mant_dig	decN_max	decN_true_min
decN_min_exp	DECN_EPSILON	
decN_max_exp	decN_min	

After 7.6#3a, insert the paragraph:

[3b] The following identifiers are declared only if <u>STDC_WANT_IEC_60559_DFP_EXT</u> is defined as a macro at the point in the source file where <fenv.h> is first included:

fe dec getround	fe dec setround
[_]	

Change 7.12#1a from:

	FP_INT_UPWARD	FP_FAST_FSUB
	FP_INT_DOWNWARD	FP_FAST_FSUBL
	FP_INT_TOWARDZERO	FP_FAST_DSUBL
	FP_INT_TONEARESTFROMZERO	FP_FAST_FMUL
20	FP_INT_TONEAREST	FP_FAST_FMULL
	FP_LLOGB0	FP_FAST_DMULL
	FP_LLOGBNAN	FP_FAST_FDIV
	SNANF	FP_FAST_FDIVL
	SNAN	FP_FAST_DDIVL
25	SNANL	FP_FAST_FSQRT
	FP_FAST_FADD	FP_FAST_FSQRTL
	FP_FAST_FADDL	FP_FAST_DSQRTL
	FP_FAST_DADDL	
		II_IASI_DSQAID

	iseqsig	fmaxmagf	ffmal
	iscanonical	fmaxmagl	dfmal
	issignaling	fminmag	fsqrt
	issubnormal	fminmagf	fsqrtl
5	iszero	fminmagl	dsqrtl
	fromfp	nextup	totalorder
	fromfpf	nextupf	totalorderf
	fromfpl	nextupl	totalorderl
	ufromfp	nextdown	totalordermag
10	ufromfpf	nextdownf	totalordermagf
	ufromfpl	nextdownl	totalordermagl
	fromfpx	fadd	canonicalize
	fromfpxf	faddl	canonicalizef
	fromfpxl	daddl	canonicalizel
15	ufromfpx	fsub	getpayload
	ufromfpxf	fsubl	getpayloadf
	ufromfpxl	dsubl	getpayloadl
	roundeven	fmul	setpayload
	roundevenf	fmull	setpayloadf
20	roundevenl	dmull	setpayloadl
	llogb	fdiv	setpayloadsig
	llogbf	fdivl	setpayloadsigf
	llogbl	ddivl	setpayloadsigl
	fmaxmag	ffma	
05	=		

25

to:

<math.h> is first included:

30	FP_INT_UPWARD	FP_LLOGBNAN
	FP_INT_DOWNWARD	iseqsig
	FP_INT_TOWARDZERO	iscanonical
	FP_INT_TONEARESTFROMZERO	issignaling
	FP_INT_TONEAREST	issubnormal
35	FP_LLOGB0	iszero

	SNANF	ufromfpxf	dmull
5	SNAN	ufromfpxl	fdiv
	SNANL	roundeven	fdivl
	FP FAST FADD	roundevenf	ddivl
	FP FAST FADDL	roundevenl	ffma
	FP FAST DADDL	llogb	ffmal
10	FP FAST FSUB	llogbf	dfmal
	FP FAST FSUBL	llogbl	fsqrt
	FP FAST DSUBL	fmaxmaq	fsqrtl
	FP FAST FMUL	fmaxmaqf	dsgrtl
	FP FAST FMULL	fmaxmaql	totalorder
15	FP FAST DMULL	fminmag	totalorderf
	FP FAST FDIV	fminmaqf	totalorderl
	FP FAST FDIVL	fminmagl	totalordermag
	FP FAST DDIVL	nextup	totalordermagf
	FP FAST FSQRT	nextupf	totalordermagl
20	FP FAST FSQRTL	nextupl	canonicalize
	FP FAST DSQRTL	nextdown	canonicalizef
	fromfp	nextdownf	canonicalizel
	fromfpf	nextdownl	getpayload
	fromfpl	fadd	getpayloadf
25	ufromfp	faddl	getpayloadl
	ufromfpf	daddl	setpayload
	ufromfpl	fsub	setpayloadf
	fromfpx	fsubl	setpayloadl
	fromfpxf	dsubl	setpayloadsig
30	fromfpxl	fmul	setpayloadsigf
	ufromfpx	fmull	setpayloadsigl

35	_Decimal32_t	DEC_INFINITY
	Decimal64_t	DEC_NAN

and for $N = 32$	2. 64. 128:
------------------	-------------

	HUGE VAL D N	modfdN	remainderdN
	SNANDN	scalbndN	copysigndN
5	FP FAST FMADN	scalblndN	nandN
C C	acosdN	cbrtdN	nextafterdN
	asindN	fabsdN	nexttowarddN
	atandN	hypotdN	nextupdN
	atan2dN	powdN	nextdowndN
10	cosdN	sgrtdN	canonicalizedN
	sindN	erfdN	fdimdN
	tandN	erfcdN	fmaxdN
	acoshdN	lgammadN	fmindN
	asinhdN	tgammadN	fmaxmagd N
15	atanhdN	ceildN	fminmagdN
	coshdN	floordN	fmadN
	$\mathtt{sinhd}N$	nearby $intdN$	totalorderdN
	tanhdN	rintdN	totalordermagd N
	expdN	lrintdN	getpayloadd N
20	exp2dN	llrintdN	${\tt setpayloadd} N$
	expmldN	rounddN	${\tt setpayloadsigd} N$
	frexpdN	lrounddN	quantized N
	ilogbdN	llrounddN	samequantumdN
	llogbdN	truncdN	quantum dN
25	ldexpdN	roundevendN	llquantexpdN
	logdN	fromfpdN	encodedecdN
	log10dN	ufromfpdN	decodedecdN
	log1pdN	fromfpxdN	encodebindN
	log2dN	ufromfpxdN	decodebind N
30	logbdN	fmoddN	
	and for $(M, N) = (22, 64)$	2 4 2 0 \ (6 4 4 2 0 \);	
	and for $(M,N) = (32,64), (32,64)$	2,120), (04,120).	
	FP FAST $DMADDDN$	FP FAST D M FMAD N	d <i>M</i> muldN
35	FP_FAST_DMSUBDN	fp_fast_dMsqrtdN	dMdivdN
	FP_FAST_DMMULDN	dMadddN	dMfmadN
	FP_FAST_DMDIVDN	dMsubdN	dMsqrtdN
	In 7.20#4a, change:		

[4a] The following identifiers are defined only if <u>STDC_WANT_IEC_60559_BFP_EXT</u> is defined as a macro at the point in the source file where <stdint.h> is first included:

to:

40

45

[4a] The following identifiers are defined only if <u>__STDC_WANT_IEC_60559_BFP_EXT_</u> or <u>__STDC_WANT_IEC_60559_DFP_EXT_</u> is defined as a macro at the point in the source file where <stdint.h> is first included:

After 7.22#1a, insert the paragraph:

	strfromd32	strfromd128	strtod64
50	strfromd64	strtod32	strtod128

Change 7.25#1a from:

[1a] The following identifiers are defined as type-generic macros only if <u>STDC_WANT_IEC_60559_BFP_EXT</u> is defined as a macro at the point in the source file where <tgmath.h> is first included:

5	roundeven	fromfpx	fmul
	llogb	ufromfpx	dmul
	fmaxmag	totalorder	fdiv
	fminmag	totalordermag	ddiv
	nextup	fadd	ffma
10	nextdown	dadd	dfma
	fromfp	fsub	fsqrt
	ufromfp	dsub	dsqrt

to:

15

30

[1a] The following identifiers are defined as type-generic macros only if ______STDC_WANT_IEC_60559_BFP_EXT__ or __STDC_WANT_IEC_60559_DFP_EXT__ is defined as a macro at the point in the source file where <tgmath.h> is first included:

	roundeven	nextup	fromfpx
20	llogb	nextdown	ufromfpx
	fmaxmag	fromfp	totalorder
	fminmag	ufromfp	totalordermag

fadd	fmul	ffma
dadd	dmul	dfma
fsub	fdiv	fsqrt
dsub	ddiv	dsqrt

d32add	d64add	quantize
d32sub	d64sub	samequantum
d32mul	d64mul	quantum
d32div	d64div	llquantexp
d32fma	d64fma	
d32sqrt	d64sqrt	
	d32sub d32mul d32div d32fma	d32sub d64sub d32mul d64mul d32div d64div d32fma d64fma

40 6 Decimal floating types

Within the type hierarchy, decimal floating types are basic types, real types, and arithmetic types.

This part of Technical Specification 18661 introduces the term *standard floating types* to refer to the types **float**, **double**, and **long double**, which are the floating types the C Standard requires unconditionally.

NOTE C does not specify a radix for float, double, and long double. An implementation can choose the representation of float, double, and long double to be the same as the decimal floating types.

Regardless of the representation, the decimal floating types are distinct from the types float, double, and long double.

NOTE This Part of Technical Specification 18661 does not define decimal complex types or decimal imaginary types. The three complex types remain as float _Complex, double _Complex, and long double _Complex, and the three imaginary types remain as float _Imaginary, double _Imaginary, and long double _Imaginary.

Changes to C11 + TS18661-1:

Change the first sentence of 6.2.5#10 from:

[10] There are three *real floating types*, designated as float, double, and long double.

10 to:

15

5

[10] There are three standard floating types, designated as float, double, and long double.

Add the following paragraphs after 6.2.5#10:

[10b] The standard floating types and the decimal floating types are collectively called the *real floating types*.

In 6.2.5#10a, attach a footnote to the wording:


they have the IEC 60559 formats: decimal32

20 where the footnote is:

*) IEC 60559 specifies decimal32 as a data-interchange format that does not require arithmetic support; however, __Decimal32 is a fully supported arithmetic type.

Add the following to 6.4.1 Keywords:

25



Add the following to 6.7.2 Type specifiers:

30 type-specifier. __Decimal32 __Decimal64 __Decimal128

- 35 Add the following bullets in 6.7.2#2 Constraints:
 - _Decimal32
 - _Decimal64
 - _Decimal128

Add the following after 6.7.2#3:

Add the following after 6.5#8:

[8a] Operators involving decimal floating types are evaluated according to the semantics of IEC 60559, including production of results with the preferred quantum exponent as specified in IEC 60559.

7 Characteristics of decimal floating types <float.h>

IEC 60559 defines a general model for floating-point data, specifies formats (both binary and decimal) for the data, and defines encodings for the formats.

The three decimal floating types correspond to decimal formats defined in IEC 60559 as follows:

— _Decimal32 is a *decimal32* format, which is encoded in 32 bits

- _Decimal64 is a *decimal64* format, which is encoded in 64 bits
- _Decimal128 is a *decimal128* format, which is encoded in 128 bits
- 15 The value of a finite number is given by (−1)^{sign} x significand x 10^{exponent}. Refer to IEC 60559 for details of the format.

These formats are characterized by the length of the significand and the maximum exponent. Note that, for decimal IEC 60559 decimal formats, trailing zeros in the significand are significant; i.e., 1.0 is equal to but can be distinguished from 1.00. The table below shows these characteristics by type:

20

5

Table 1 – Format characteristics

Туре	_Decimal32	_Decimal64	_Decimal128
Significand length in digits	7	16	34
Maximum Exponent (E _{max})	97	385	6145
Minimum Exponent (E _{min})	-94	-382	-6142

The maximum and minimum exponents in the table are for floating-point numbers expressed with significands less than 1, as in the C11 model (5.2.4.2.2). They differ (by 1) from the maximum and minimum exponents in the IEC 60559 standard, where normalized floating-point numbers are expressed with one significant digit to the left of the radix point.

25 the left of the

If the macro <u>STDC_WANT_IEC_60559_DFP_EXT</u> is defined at the point in the source file where the header <float.h> is first included, the header <float.h> shall define several macros that expand to various limits and parameters of the decimal floating types. The names and meaning of these macros are similar to the corresponding macros for standard floating types.

30 Changes to C11 + TS18661-1:

In 5.2.4.2.2#6, append the sentence:

Decimal floating-point operations have stricter requirements.

In 5.2.4.2.2#7, change:

All except CR_DECIMAL_DIG (F.5), DECIMAL_DIG, FLT_EVAL_METHOD, FLT_RADIX. and FLT_ROUNDS have separate names for all three floating-point types. The floating-point model representation is provided for all values except FLT_EVAL_METHOD and FLT_ROUNDS.

5 to:

All except CR_DECIMAL_DIG (F.5), DECIMAL_DIG, DEC_EVAL_METHOD, FLT_EVAL_METHOD, FLT_RADIX, and FLT_ROUNDS have separate names for all real floating types. The floating-point model representation is provided for all values except DEC_EVAL_METHOD, FLT_EVAL_METHOD, and FLT ROUNDS.

10 After 5.2.4.2.2#7, insert the paragraph:

[7a] The remainder of this subclause specifies characteristics of standard floating types.

In 5.2.4.2.2#8, change:

[8] The rounding mode for floating-point addition is characterized by the implementation-defined value of **FLT_ROUNDS**

15 to:

[8] The rounding mode for floating-point addition for standard floating types is characterized by the implementation-defined value of **FLT_ROUNDS**

Add the following after 5.2.4.2.2:

5.2.4.2.2a Characteristics of decimal floating types in <float.h>

20 [1] This subclause specifies macros in <float.h> that provide characteristics of decimal floating types in terms of the model presented in 5.2.4.2.2. The prefixes DEC32_, DEC64_, and DEC128_ denote the types _Decimal32, _Decimal64, and _Decimal128 respectively.

[2] **DEC_EVAL_METHOD** is the decimal floating-point analogue of **FLT_EVAL_METHOD** (5.2.4.2.2). Its implementation-defined value characterizes the use of evaluation formats for decimal floating types:

- 25 **-1** indeterminable;
 - **0** evaluate all operations and constants just to the range and precision of the type;
 - 1 evaluate operations and constants of type _Decimal32 and _Decimal64 to the range and precision of the _Decimal64 type, evaluate _Decimal128 operations and constants to the range and precision of the _Decimal128 type;
- 30 **2** evaluate all operations and constants to the range and precision of the **_Decimal128** type.

[3] The integer values given in the following lists shall be replaced by constant expressions suitable for use in **#if** preprocessing directives:

- radix of exponent representation, b(=10)
- 35 For the standard floating types, this value is implementation-defined and is specified by the macro **FLT_RADIX**. For the decimal floating types there is no corresponding macro, since the value 10 is an inherent property of the types. Wherever **FLT RADIX** appears in a description of a function

that has versions that operate on decimal floating types, it is noted that for the decimal floatingpoint versions the value used is implicitly 10, rather than **FLT RADIX**.

- number of digits in the coefficient
- 5 DEC32 MANT DIG 7 DEC64 MANT DIG 16 DEC128 MANT DIG 34 minimum exponent 10 DEC32 MIN EXP -94 DEC64 MIN EXP -382 DEC128 MIN EXP -6142 15 maximum exponent DEC32 MAX EXP 97 DEC64 MAX EXP 385 DEC128 MAX EXP 6145 — maximum representable finite decimal floating-point number (there are 6, 15 and 33 9's after the 20 decimal points respectively) DEC32 MAX 9.999999E96DF DEC64 MAX 9.999999999999998384DD 25 DEC128 MAX — the difference between 1 and the least value greater than 1 that is representable in the given floating type DEC32 EPSILON 30 1E-6DF DEC64 EPSILON 1E-15DD DEC128 EPSILON 1E-33DL minimum normalized positive decimal floating-point number 35 DEC32 MIN 1E-95DF DEC64 MIN 1E-383DD DEC128 MIN 1E-6143DL - minimum positive subnormal decimal floating-point number 40 DEC32 TRUE MIN 0.00001E-95DF DEC64 TRUE MIN 0.0000000000001E-383DD DEC128 TRUE MIN 45 [4] For decimal floating-point arithmetic, it is often convenient to consider an alternate equivalent model where the significand is represented with integer rather than fraction digits: a floating-point number (x) is defined by the model

$$x = sb^{(e-p)} \sum_{k=1}^{p} f_{k}b^{(p-k)}$$

50 where s, b, e, p, and f_k are as defined in 5.2.4.2.2, and b = 10.

[5] The term *quantum exponent* refers to q = e - p and *coefficient* to $c = f_1 f_2 \dots f_p$, an integer between 0 and $b^p - 1$ inclusive. Thus, $x = s * c * b^q$ is represented by the triple of integers (*s*, *c*, *q*). The term *quantum* refers to the value of a unit in the last place of the coefficient. Thus, the quantum of *x* is b^q .

Table 2 – Quantum exponent ranges

Туре	_Decimal32	_Decimal64	_Decimal128
Maximum Quantum Exponent (q _{max})	90	369	6111
Minimum Quantum Exponent (q _{min})	-101	-398	-6176

5

10

15

[6] For binary floating-point arithmetic following IEC 60559, representations in the model described in 5.2.4.2.2 that have the same numerical value are indistinguishable in the arithmetic. However, for decimal floating-point arithmetic, representations that have the same numerical value but different quantum exponents, e.g., (1, 10, -1) representing 1.0 and (1, 100, -2) representing 1.00, are distinguishable. To facilitate exact fixed-point calculation, operation results that are of decimal floating type have a *preferred quantum exponent*, as specified in IEC 60559, which is determined by the quantum exponents of the operands if they have decimal floating types (or by specific rules for conversions from other types). The table below gives rules for determining preferred quantum exponent. When exact, these operations produce a result with their preferred quantum exponent, or as close to it as possible within the limitations of the type. When inexact, these operations produce a result with the preferred quantum exponent for addition is the minimum of the quantum exponents of the operands. Hence (1, 123, -2) + (1, 4000, -3) = (1, 5230, -3) or 1.23 + 4.000 = 5.230.

20 [7] The following table shows, for each operation, how the preferred quantum exponents of the operands, Q(x), Q(y), etc., determine the preferred quantum exponent of the operation result:

Decimal operation (shown without suffixes) Preferred quantum exponent of result roundeven, round, trunc, ceil, floor, $max(Q(\mathbf{x}),0)$ rint, nearbyint nextup, nextdown, nextafter, nexttoward least possible remainder $min(Q(\mathbf{x}),Q(\mathbf{y}))$ $Q(\mathbf{x})$ if \mathbf{x} gives the result, fmin, fmax, fminmag, fmaxmag $Q(\mathbf{y})$ if \mathbf{y} gives the result Q(x)+nscalbn, scalbln Q(x)+exp ldexp logb 0 +, d32add, d64add $min(Q(\mathbf{x}),Q(\mathbf{y}))$ -, d32sub, d64sub $min(Q(\mathbf{x}),Q(\mathbf{y}))$ *, d32mul, d64mul $Q(\mathbf{x})+Q(\mathbf{y})$ $Q(\mathbf{x}) - Q(\mathbf{y})$ /, d32div, d64div sqrt, d32sqrt, d64sqrt floor(Q(x)/2)fma, d32fma, d64fma $\min(Q(\mathbf{x})+Q(\mathbf{y}),Q(\mathbf{z}))$ conversion from integer type 0 exact conversion from non-decimal floating type 0 inexact conversion from non-decimal floating least possible type conversion between decimal floating types $Q(\mathbf{x})$ *cx returned by canonicalize Q(*x)see 7.22.1.3a strtod, wcstod, scanf, floating constants of decimal floating type -(x) $Q(\mathbf{x})$ fabs $Q(\mathbf{x})$ copysign $Q(\mathbf{x})$ quantize Q(y) quantum $Q(\mathbf{x})$ *encptr returned by encodedec, encodebin Q(*xptr) *xptr returned by decodedec, decodebin Q(*encptr) fmod $min(Q(\mathbf{x}),Q(\mathbf{y}))$ fdim $min((Q(\mathbf{x}),Q(\mathbf{y})) \text{ if } \mathbf{x} > \mathbf{y},$ 0 if **x**≤y cbrt floor(Q(x)/3)hypot $min(Q(\mathbf{x}),Q(\mathbf{y}))$ pow $floor(\mathbf{y} \times Q(\mathbf{x}))$ modf Q(value) max(Q(value),0)*iptr returned by modf frexp Q(value) if value=0, - (length of coefficient of value) otherwise returned 0 if pl does not represent a valid payload, *res by setpayload, setpayloadsig not applicable otherwise (NaN returned) getpayload 0 if ***x** is a NaN. unspecified otherwise transcendental functions 0

Table 3 – Preferred quantum exponents

8 Operation binding

The table and subsequent text in F.3 as specified in Part 1 of Technical Specification 18661, with the further change below, show how the C decimal operations specified in this document, Part 2 of Technical Specification 18661, provide the operations required by IEC 60559 for decimal floating-point arithmetic.

5 **Change to C11 + TS18661-1**:

After F.3#10 (see Part 1 of Technical Specification 18661), append the following:

[13] Decimal versions of the C **remquo** function are not provided. (The C decimal **remainder** functions provide the remainder operation defined by IEC 60559.)

10

25

30

[14] The C quantizedN functions (7.12.11a.1) provide the quantize operation defined in IEC 60559 for decimal floating-point arithmetic.

[15] The binding for the convertFormat operation applies to all conversions among IEC 60559 formats. Therefore, for implementations that conform to Annex F, conversions between decimal floating types and standard floating types with IEC 60559 formats are correctly rounded and raise floating-point exceptions as specified in IEC 60559.

15 [16] IEC 60559 specifies the convertFromHexCharacter and convertToHexCharacter operations only for binary floating-point arithmetic.

[17] The C integer constant 10 provides the radix operation defined in IEC 60559 for decimal floating-point arithmetic.

[18] The C samequantumdN functions (7.12.11a.2) provide the sameQuantum operation defined in IEC 60559 for decimal floating-point arithmetic.

[19] The C fe_dec_getround (7.6.3.3) and fe_dec_setround (7.6.3.4) functions provide the getDecimalRoundingDirection and setDecimalRoundingDirection operations defined in IEC 60559 for decimal floating-point arithmetic. The macros (7.6) FE_DEC_DOWNWARD, FE_DEC_TONEAREST, FE_DEC_TONEARESTFROMZERO, FE_DEC_TOWARDZERO, and FE_DEC_UPWARD, which are used in conjunction with the fe_dec_getround and fe_dec_setround functions, represent the IEC 60559 rounding-direction attributes roundTowardNegative, roundTiesToEven, roundTiesToAway, roundTowardZero, and roundTowardPositive, respectively.

[20] The C quantum N (7.12.11a.3) and llquantexpdN (7.12.11a.4) functions compute the quantum and the (quantum) exponent q defined in IEC 60559 for decimal numbers viewed as having integer significands.

[21] The C encodedecdN (7.12.11b.1) and decodedecdN (7.12.11b.2) functions provide the encodeDecimal and decodeDecimal operations defined in IEC 60559 for decimal floating-point arithmetic.

[22] The C encodebindN (7.12.11b.3) and decodebindN (7.12.11b.4) functions provide the encodeBinary and decodeBinary operations defined in IEC 60559 for decimal floating-point arithmetic.

9 Conversions

9.1 Conversions between decimal floating and integer types

40

For conversions between real floating and integer types, C11 6.3.1.4 leaves the behavior undefined if the conversion result cannot be represented (Annex F.3 and F.4 define the behavior). To help writing portable code, this Part of Technical Specification 18661 provides defined behavior for decimal floating types.

Changes to C11 + TS18661-1:

Change the first sentence of 6.3.1.4#1 from:

[1] When a finite value of real floating type is converted to an integer type ...

to:

[1] When a finite value of standard floating type is converted to an integer type ...

Add the following paragraph after 6.3.1.4#1:

[1a] When a finite value of decimal floating type is converted to an integer type other than <u>Bool</u>, the fractional part is discarded (i.e., the value is truncated toward zero). If the value of the integral part cannot be represented by the integer type, the "invalid" floating-point exception shall be raised and the result of the conversion is unspecified.

10

25

30

35

5

Change the first sentence of 6.3.1.4#2 from:

[2] When a value of integer type is converted to a real floating type, ...

to:

[2] When a value of integer type is converted to a standard floating type, ...

15 Add the following paragraph after 6.3.1.4#2:

[2a] When a value of integer type is converted to a decimal floating type, if the value being converted can be represented exactly in the new type, it is unchanged. If the value being converted cannot be represented exactly, the result shall be correctly rounded with exceptions raised as specified in IEC 60559.

20 9.2 Conversions among decimal floating types, and between decimal floating and standard floating types

In the following change to C11 + TS18661-1, the specification of conversions among decimal floating types is similar to the existing one for float, double, and long double, except that when the result cannot be represented exactly, the specification requires correct rounding. It also requires correct rounding for conversions from standard to decimal floating types. The specification in Annex F requires correct rounding for conversions from decimal to the standard floating types that conform to IEC 60559.

Change to C11 + TS18661-1:

Replace 6.3.1.5#1:

[1] When a value of real floating type is converted to a real floating type, if the value being converted can be represented exactly in the new type, it is unchanged. If the value being converted is in the range of values that can be represented but cannot be represented exactly, the result is either the nearest higher or nearest lower representable value, chosen in an implementation-defined manner. If the value being converted is outside the range of values that can be represented, the behavior is undefined. Results of some implicit conversions (6.3.1.8, 6.8.6.4) may be represented in greater range and precision than that required by the new type.

with:

[1] When a value of real floating type is converted to a real floating type, if the value being converted can be represented exactly in the new type, it is unchanged.

5

10

[2] When a value of real floating type is converted to a standard floating type, if the value being converted is in the range of values that can be represented but cannot be represented exactly, the result is either the nearest higher or nearest lower representable value, chosen in an implementation-defined manner. If the value being converted is outside the range of values that can be represented, the behavior is undefined.

[3] When a value of real floating type is converted to a decimal floating type, if the value being converted cannot be represented exactly, the result is correctly rounded with exceptions raised as specified in IEC 60559

[4] Results of some implicit conversions (6.3.1.8, 6.8.6.4) may be represented in greater range and precision than that required by the new type.

9.3 Conversions between decimal floating and complex types

This is covered by C11 6.3.1.7.

9.4 Usual arithmetic conversions

In an application that is written using decimal floating-point arithmetic, mixed operations between decimal and other real types are likely to occur only when interfacing with other languages, calling existing libraries written for binary floating-point arithmetic, or accessing existing data. Determining the common type for mixed operations is difficult because ranges overlap; therefore, mixed mode operations are not allowed and the programmer must use explicit casts. Implicit conversions are allowed only for simple assignment, return statement, and in argument passing involving prototyped functions.

20 Change to C11 + TS18661-1:

Insert the following in 6.3.1.8#1, after "This pattern is called the usual arithmetic conversions:"

If one operand has decimal floating type, the other operand shall not have standard floating, complex, or imaginary type.

First, if the type of either operand is _Decimal128, the other operand is converted to _Decimal128.

25 Otherwise, if the type of either operand is <u>_Decimal64</u>, the other operand is converted to <u>_Decimal64</u>.

Otherwise, if the type of either operand is <u>_______</u> becimal32, the other operand is converted to <u>______</u> Decimal32.

If there are no decimal floating types in the operands:

30 First, if the corresponding real type of either operand is long double, the other operand is converted, without ... <the rest of 6.3.1.8#1 remains the same>

9.5 Default argument promotion

There is no default argument promotion specified for the decimal floating types. Default argument promotion covered in C11 6.5.2.2 [6] and [7] remains unchanged, and applies to standard floating types only.

35 **10 Constants**

New suffixes are added to denote decimal floating constants: df and DF for _Decimal32, dd and DD for Decimal64, and dl and DL for Decimal128.

This specification does not carry forward two features introduced in TR 24732: the **FLOAT CONST DECIMAL64** pragma and the **d** and **D** suffixes for floating constants. The pragma changed the

interpretation of unsuffixed floating constants between double and _Decimal64. The suffixes provided a way to designate double floating constants so that the pragma would not affect them. The pragma is not included because of its potential for inadvertently reinterpreting constants. Without the pragma, the suffixes are no longer needed. Also, significant implementations use the d and D suffixes for other purposes.

5 Changes to C11 + TS18661-1:

Change *floating-suffix* in 6.4.4.2 from:

floating-suffix: one of flFL

to:

```
10 floating-suffix: one of
f l F L df dd dl DF DD DL
```

Add the following after 6.4.4.2#2:

Constraints

[2a] A floating-suffix df, dd, dl, DF, DD, or DL shall not be used in a hexadecimal-floating-constant.

15 Add the following paragraph after 6.4.4.2#4:

[4a] If a floating constant is suffixed by df or DF, it has type _Decimal32. If suffixed by dd or DD, it has type _Decimal64. If suffixed by dl or DL, it has type _Decimal128.

Add the following paragraph after 6.4.4.2#5:

[5a] Floating constants of decimal floating type that have the same numerical value but different quantum exponents have distinguishable internal representations. The quantum exponent is specified to be the same as for the corresponding strtod32, strtod64, or strtod128 function for the same numeric string.

11 Arithmetic operations

11.1 Operators

25 The operators *Add* (C11 6.5.6), *Subtract* (C11 6.5.6), *Multiply* (C11 6.5.5), *Divide* (C11 6.5.5), *Relational operators* (C11 6.5.8), *Equality operators* (C11 6.5.9), *Unary Arithmetic operators* (C11 6.5.3.3), and *Compound Assignment operators* (C11 6.5.16.2) when applied to decimal floating type operands shall follow the semantics as defined in IEC 60559.

Changes to C11 + TS18661-1:

30 Add the following after 6.5.5#2:

[2a] If either operand has decimal floating type, the other operand shall not have standard floating type, complex type, nor imaginary type.

Add the following after 6.5.6#3:

[3a] If either operand has decimal floating type, the other operand shall not have standard floating type, complex type, nor imaginary type.

5

Add the following after 6.5.8#2:

[2a] If either operand has decimal floating type, the other operand shall not have standard floating type.

Add the following after 6.5.9#2:

[2a] If either operand has decimal floating type, the other operand shall not have standard floating type, complex type, nor imaginary type.

Add the following bullet to 6.5.15#3:

- one operand has decimal floating type, and the other has arithmetic type other than standard floating type, complex type, and imaginary type;
- 10 Add the following after 6.5.16.2#2:

[2a] If either operand has decimal floating type, the other operand shall not have standard floating type, complex type, nor imaginary type.

11.2 Functions

The headers and library supply a number of functions and function-like macros that support decimal floatingpoint arithmetic with the semantics specified in IEC 60559, including producing results with the preferred quantum exponent where appropriate. That support is provided by the following:

From C11 <math.h>, with changes in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

sqrt, fma, fabs, fmax, fmin, ceil, floor, trunc, round, rint, lround, llround, ldexp, frexp, ilogb, logb, scalbn, scalbln, copysign, remainder, isnan, isinf, isfinite, isnormal, signbit, fpclassify, isunordered, isgreater, isgreaterequal, isless, islessequal and islessgreater.

From the <math.h> extensions specified in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

- 25 roundeven, nextup, nextdown, fminmag, fmaxmag, llogb, fadd, faddl, daddl, fsub, fsubl, dsubl, fmul, fmull, dmull, fdiv, fdivl, ddivl, fsqrt, fsqrtl, dsqrtl, ffma, ffmal, dfmal, fromfp, ufromfp, fromfpx, ufromfpx, canonicalize, iseqsig, issignaling, issubnormal, iscanonical, iszero, totalorder, totalordermag, getpayload, setpayload, and setpayloadsig.
- 30 The <math.h> extensions specified below in 12.4 for the decimal-specific functions:

quantized N, samequantumd N, quantumd N, llquantexpd N, encoded ecd N, decoded ecd N, encode bind N, and decode bind N.

From C11 <fenv.h>, facilities dealing with decimal context:

feraiseexcept, feclearexcept, fetestexcept, fesetexceptflag, fegetexceptflag, 35 fesetenv, fegetenv, feupdateenv, and feholdexcept.

From the **<fenv.h>** extensions specified in Part 1 of Technical Specification 18661, facilities dealing with decimal context:

fetestexceptflag, fesetexcept, fegetmode, and fesetmode.

From the **<fenv.h>** extensions specified in this Part of Technical Specification 18661, facilities dealing with decimal context:

fe_dec_getround and fe_dec_setround.

From <stdio.h>, decimal floating-point modified format specifiers for:

5 The printf/scanf family of functions.

From <stdlib.h> and <wchar.h>, with changes in Part 1 of Technical Specification 18661, the decimal floating-point versions of:

strtod and wcstod.

From the <stdlib.h> extensions specified in Part 1 of Technical Specification 18661, the decimal floatingpoint versions of:

strfromd.

From <wchar.h>, decimal floating-point modified format specifiers for:

The wprintf/wscanf family of functions.

11.3 Conversions

15 Conversions between different floating types and conversions to and from integer types are covered in clause 9.

11.4 Expression transformations

The following changes to C11 + TS18661-1 alert implementors that some expression transformations must be avoided in order to preserve the quantum exponent (7) of decimal floating-point numbers.

20 Changes to C11 + TS18661-1:

In F.9.2, insert before paragraph #1:

[0] Valid expression transformations must preserve numerical values.

In F.9.2, insert at the beginning of paragraph #1:

[1] The equivalences noted below apply to expressions of standard floating types.

25 In F.9.2, append:

[2] For expressions of decimal floating types, transformations must preserve quantum exponents, as well as numerical values (5.2.4.2.2a).

[3] EXAMPLE **1.** $\times x \rightarrow x$ is valid for decimal floating-point expressions x, but **1.0** $\times x \rightarrow x$ is not:

$$1. \times 12.34 = (1, 1, 0) \times (1, 1234, -2) = (1, 1234, -2) = 12.34$$

1.0 × 12.34 = (1, 10, −1) x (1, 1234, −2) = (1, 12340, −3) = 12.340

The results are numerically equal, but have different quantum exponents, hence have different values.

12 Library

5

15

12.1 Standard headers

The functions, macros, and types declared or defined in Clause 12 and its subclauses are only declared or defined by their respective headers if the macro <u>STDC_WANT_IEC_60559_DFP_EXT</u> is defined at the point in the source file where the appropriate header is first included.

12.2 Decimal floating-point environment in <fenv.h>

The floating-point environment specified in C11 7.6 applies to operations for both standard floating types and decimal floating types. This is to implement the *context* defined in IEC 60559. The existing general C11 specification gives flexibility to an implementation on which part of the environment is accessible to programs.

10 Annex F requires support for all the (binary) rounding directions and exception flags (for operations for standard floating types). This document requires support for all the rounding directions and exceptions flags for operations for decimal floating types.

IEC 60559 requires separate rounding modes for binary and decimal floating-point operations. This document requires a separate rounding mode for decimal floating-point operations if the standard floating types are not decimal, and it allows the implementation to define whether the rounding modes are separate or the same if the standard floating types are decimal.

Table 4 – Rounding mode macros

For decimal floating types	For standard floating types	IEC 60559
FE_DEC_TOWARDZERO	FE_TOWARDZERO	Toward zero
FE_DEC_TONEAREST	FE_TONEAREST	To nearest, ties to even
FE_DEC_UPWARD	FE_UPWARD	Toward plus infinity
FE_DEC_DOWNWARD	FE_DOWNWARD	Toward minus infinity
FE_DEC_TONEARESTFROMZERO	n/a	To nearest, ties away from zero

Changes to C11 + TS18661-1:

Add the following after 7.6#6:

[6a] Decimal floating-point operations and IEC 60559 binary floating-point operations (Annex F) access the same floating-point exception status flags.

In 7.6#8, delete the sentence (and retain footnote 211 at the end of the paragraph):

The defined macros expand to integer constant expressions whose values are distinct nonnegative values.

Add the following after 7.6#8:

[8a] Each of the macros

FE_DEC_DOWNWARD FE_DEC_TONEAREST FE_DEC_TONEARESTFROMZERO FE_DEC_TOWARDZERO FE_DEC_UPWARD

35

30

is defined for use with the fe_dec_getround and fe_dec_setround functions for getting and setting the dynamic rounding direction mode, and with the FENV_DEC_ROUND rounding control pragma (7.6.1b) for specifying a constant rounding direction, for decimal floating-point operations. The decimal rounding direction affects all (inexact) operations that produce a result of decimal floating

type and all operations that produce an integer or character sequence result and have an operand of decimal floating type, unless stated otherwise. The macros expand to integer constant expressions whose values are distinct nonnegative values.

[8b] During translation, constant rounding direction modes for decimal floating-point arithmetic are in effect where specified. Elsewhere, during translation the decimal rounding direction mode is **FE_DEC_TONEAREST**.

[8c] At program startup the dynamic rounding direction mode for decimal floating-point arithmetic is initialized to **FE DEC TONEAREST**.

In 7.6.1a#2, change the first sentence from:

10 The **FENV_ROUND** pragma provides a means to specify a constant rounding direction for floating-point operations within a translation unit or compound statement.

to:

The **FENV_ROUND** pragma provides a means to specify a constant rounding direction for floating-point operations for standard floating types within a translation unit or compound statement.

15 In 7.6.1a#3, change the first sentence from:

direction shall be one of the rounding direction macro names defined in 7.6, or FE DYNAMIC.

to:

direction shall be one of the names of the supported rounding direction macros for operations for standard floating types (7.6), or **FE_DYNAMIC.**

20 In 7.6.1a#4, replace the first sentence:

Within the scope of an **FENV_ROUND** directive establishing a mode other than **FE_DYNAMIC**, all floating-point operators, ...

with:

25

The **FENV_ROUND** directive affects operations for standard floating types. Within the scope of an **FENV_ROUND** directive establishing a mode other than **FE_DYNAMIC**, floating-point operators, ...

In 7.6.1a#4, change the table title from:

Functions affected by constant rounding modes

to:

Functions affected by constant rounding modes - for standard floating types

30 In 7.6.1a#4, change the sentence following the table from:

Each <math.h> functon listed in the table above indicates the family of functions of all supported types (for example, acosf and acosl as well as acos).

to:

35

Each <math.h> functon listed in the table above indicates the family of functions of all standard floating types (for example, acosf and acosl as well as acos).

In 7.6.1a#4, change the last sentence from:

Floating constants (6.4.4.2) that occur in the scope of a constant rounding mode shall be interpreted according to that mode.

to:

5 Floating constants (6.4.4.2) of a standard floating type that occur in the scope of a constant rounding mode shall be interpreted according to that mode.

After 7.6.1a, insert:

7.6.1b Decimal rounding control pragma

Synopsis

10 [1] #define __STDC_WANT_IEC_60559_DFP_EXT__ #include <fenv.h> #pragma STDC FENV DEC ROUND dec-direction

Description

15 [2] The FENV_DEC_ROUND pragma is a decimal floating-point analogue of the FENV_ROUND pragma. If FLT_RADIX is not 10, the FENV_DEC_ROUND pragma affects operators, functions, and floating constants only for decimal floating types. The affected functions are listed in the table below. If FLT_RADIX is 10, whether the FENV_ROUND and FENV_DEC_ROUND pragmas alter the rounding direction of both standard and decimal floating-point operations is implementation-defined. dec-direction shall be one of the decimal rounding direction macro names (FE_DEC_DOWNWARD, FE_DEC_TONEAREST, FE_DEC_TONEARESTFROMZERO, FE_DEC_TOWARDZERO, and FE_DEC_UPWARD) defined in 7.6, to specify a constant rounding mode, or FE_DEC_DYNAMIC, to specify dynamic rounding. The corresponding dynamic rounding mode can be established by a call to fe_dec_setround.

Header	Function groups
<math.h></math.h>	acosdN, $asindN$, $atandN$, $atan2dN$
<math.h></math.h>	cosdN, sindN, tandN
<math.h></math.h>	acoshdN, asinhdN, atanhdN
<math.h></math.h>	coshdN, sinhdN, tanhdN
<math.h></math.h>	expdN, $exp2dN$, $expm1dN$
<math.h></math.h>	logdN, log10dN, log1pdN, log2dN
<math.h></math.h>	scalbnd N , scalblnd N , ldexpd N
<math.h></math.h>	$\mathtt{cbrtd}N, \mathtt{hypotd}N, \mathtt{powd}N, \mathtt{sqrtd}N$
<math.h></math.h>	erfdN, erfcdN
<math.h></math.h>	lgammad N , tgammad N
<math.h></math.h>	rintdN, nearbyintdN, lrintdN, llrintdN
<math.h></math.h>	quantizedN
<math.h></math.h>	fdimdN
<math.h></math.h>	fmadN
<math.h></math.h>	dMadddN, $dMsubdN$, $dMmuldN$, $dMdivdN$, $dMfmadN$,
	dMsqrtdN
<stdlib.h></stdlib.h>	strfromdN, strtodN
<wchar.h></wchar.h>	wcstodN
<stdio.h></stdio.h>	printf and scanf families
<wchar.h></wchar.h>	wprintf and wscanf families

Add the following after 7.6.3.2:

7.6.3.3 The fe_dec_getround function

Synopsis

```
5 [1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <fenv.h>
int fe_dec_getround(void);
```

Description

10 [2] The **fe_dec_getround** function gets the current value of the dynamic rounding direction mode for decimal floating-point operations.

Returns

15

20

25

[3] The fe_dec_getround function returns the value of the rounding direction macro representing the current dynamic rounding direction for decimal floating-point operations, or a negative value if there is no such rounding macro or the current rounding direction is not determinable.

7.6.3.4 The fe dec setround function

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <fenv.h>
int fe_dec_setround(int round);
```

Description

[2] The fe_dec_setround function sets the dynamic rounding direction mode for decimal floatingpoint operations to be the rounding direction represented by its argument round. If the argument is not equal to the value of a decimal rounding direction macro, the rounding direction is not changed.

[3] If **FLT_RADIX** is not 10, the rounding direction altered by the **fesetround** function is independent of the rounding direction altered by the **fe_dec_setround** function; otherwise if **FLT_RADIX** is 10, whether the **fesetround** and **fe_dec_setround** functions alter the rounding direction of both standard and decimal floating-point operations is implementation-defined.

30 Returns

[4] The **fe_dec_setround** function returns a zero value if and only if the argument is equal to a decimal rounding direction macro (that is, if and only if the dynamic rounding direction mode for decimal floating-point operations was set to the requested rounding direction).

12.3 Decimal mathematics in <math.h>

- The list of types, macros, and functions specified in the mathematics library is extended to handle decimal floating types. These include functions specified in C11 (7.12.4, 7.12.5, 7.12.6, 7.12.7, 7.12.8, 7.12.9, 7.12.10, 7.12.11, 7.12.12, and 7.12.13) and in Part 1 of Technical Specification 18661 (14.1, 14.2, 14.3, 14.4, 14.5, 14.8, 14.9, and 14.0). With the exception of the decimal floating-point functions listed in 11.2, which have accuracy as specified in IEC 60559, the accuracy of decimal floating-point results is implementation-defined. The implementation may state that the accuracy is unknown. All classification macros specified in C11
- 40 The implementation may state that the accuracy is unknown. All classification macros specified in C11 (7.12.3) and in Part 1 of Technical Specification 18661 (14.7) are also extended to handle decimal floating

types. The same applies to all comparison macros specified in C11 (7.12.14) and in Part 1 of Technical Specification 18661 (14.6).

The names of the functions are derived by adding suffixes d32, d64, and d128 to the double version of the function name, except for the functions that round result to narrower type (7.12.13a).

5 **Changes to C11 + TS18661-1**:

Add after 7.12#2:

[2a] The types

_Decimal32_t _Decimal64_t

10

15

are decimal floating types at least as wide as _Decimal32 and _Decimal64, respectively, and such that _Decimal64_t is at least as wide as _Decimal32_t. If DEC_EVAL_METHOD equals 0, _Decimal32_t and _Decimal64_t are _Decimal32 and _Decimal64, respectively; if DEC_EVAL_METHOD equals 1, they are both _Decimal64; if DEC_EVAL_METHOD equals 2, they are both _Decimal128; and for other values of DEC_EVAL_METHOD, they are otherwise implementation-defined.

Add after 7.12#3:

[3a] The macro

HUGE VAL D32

20 expands to a constant expression of type Decimal32 representing positive infinity. The macros

HUGE_VAL_D64 HUGE VAL D128

are respectively _Decimal64 and _Decimal128 analogues of HUGE_VAL_D32.

25 Add after 7.12#4:

[4a] The macro

DEC_INFINITY

expands to a constant expression of type _Decimal32 representing positive infinity.

Add after 7.12#5, before 7.12#5a (see Part 1 of Technical Specification 18661):

30 [5a-] The macro

DEC_NAN

expands to a constant expression of type Decimal32 representing a quiet NaN.

Add after 7.12#5a:

[5b] The decimal signaling NaN macros

SNAND32 SNAND64 SNAND128

each expands to a constant expression of the respective decimal floating type representing a signaling NaN. If a signaling NaN macro is used for initializing an object of the same type that has static or thread-local storage duration, the object is initialized with a signaling NaN value.

10 Add after 7.12#7a:

[7b] The macros

FP_FAST_FMAD32 FP_FAST_FMAD64 FP_FAST_FMAD128

15

5

are, respectively, _Decimal32, _Decimal64, and _Decimal128 analogues of FP_FAST_FMA.

[7c] The macros

	FP_FAST_D32ADDD64
	FP_FAST_D32ADDD128
20	FP_FAST_D64ADDD128
	FP_FAST_D32SUBD64
	FP_FAST_D32SUBD128
	FP_FAST_D64SUBD128
	FP_FAST_D32MULD64
25	FP_FAST_D32MULD128
	FP_FAST_D64MULD128
	FP_FAST_D32DIVD64
	FP_FAST_D32DIVD128
	FP_FAST_D64DIVD128
30	FP_FAST_D32FMAD64
	FP_FAST_D32FMAD128
	FP FAST D64FMAD128
	FP_FAST_D32SQRTD64
	FP_FAST_D32SQRTD128
35	FP_FAST_D64SQRTD128

are decimal analogues of FP_FAST_FADD, FP_FAST_FADDL, FP_FAST_DADDL, etc.

Add the following list of function prototypes to the synopsis of the respective subclauses:

7.12.4 Trigonometric functions

```
40 __Decimal32 acosd32(_Decimal32 x);
__Decimal64 acosd64(_Decimal64 x);
__Decimal128 acosd128(_Decimal128 x);
45 __Decimal32 asind32(_Decimal32 x);
__Decimal64 asind64(_Decimal64 x);
__Decimal128 asind128(_Decimal128 x);
50 __Decimal64 atand64(_Decimal64 x);
50 __Decimal128 atand128(_Decimal128 x);
```

```
_Decimal32 atan2d32(_Decimal32 y, _Decimal32 x);
            _Decimal64 atan2d64(_Decimal64 y, _Decimal64 x);
            _Decimal128 atan2d128(_Decimal128 y, _Decimal128 x);
5
            _Decimal32 cosd32(_Decimal32 x);
             Decimal64 cosd64( Decimal64 x);
            Decimal128 cosd128 ( Decimal128 x);
10
            Decimal32 sind32( Decimal32 x);
            Decimal64 sind64( Decimal64 x);
            Decimal128 sind128 ( Decimal128 x);
            Decimal32 tand32( Decimal32 x);
15
             Decimal64 tand64( Decimal64 x);
            Decimal128 tand128 ( Decimal128 x);
        7.12.5 Hyperbolic functions
            _Decimal32 acoshd32(_Decimal32 x);
            _Decimal64 acoshd64(_Decimal64 x);
20
            _Decimal128 acoshd128(_Decimal128 x);
            Decimal32 asinhd32( Decimal32 x);
            Decimal64 asinhd64( Decimal64 x);
            Decimal128 asinhd128 ( Decimal128 x);
25
            Decimal32 atanhd32( Decimal32 x);
            Decimal64 atanhd64( Decimal64 x);
            Decimal128 atanhd128 ( Decimal128 x);
30
            Decimal32 coshd32( Decimal32 x);
             Decimal64 coshd64( Decimal64 x);
            Decimal128 coshd128 ( Decimal128 x);
            Decimal32 sinhd32( Decimal32 x);
             Decimal64 sinhd64( Decimal64 x);
35
            Decimal128 sinhd128 ( Decimal128 x);
            _Decimal32 tanhd32(_Decimal32 x);
            _Decimal64 tanhd64(_Decimal64 x);
40
            Decimal128 tanhd128(_Decimal128 x);
        7.12.6 Exponential and logarithmic functions
            Decimal32 expd32( Decimal32 x);
            Decimal64 expd64 ( Decimal64 x);
            _Decimal128 expd128(_Decimal128 x);
45
            Decimal32 exp2d32( Decimal32 x);
            Decimal64 exp2d64( Decimal64 x);
            Decimal128 exp2d128 ( Decimal128 x);
            _Decimal32 expm1d32(_Decimal32 x);
50
            Decimal64 expmld64( Decimal64 x);
            _Decimal128 expm1d128(_Decimal128 x);
```

_Decimal32 frexpd32(_Decimal32 value, int *exp); 55 __Decimal64 frexpd64(_Decimal64 value, int *exp); _Decimal128 frexpd128(_Decimal128 value, int *exp);

WG 14 N1781

```
int ilogbd32(_Decimal32 x);
            int ilogbd64(_Decimal64 x);
           int ilogbd128( Decimal128 x);
5
            _Decimal32 ldexpd32(_Decimal32 x, int exp);
            Decimal64 ldexpd64( Decimal64 x, int exp);
           _Decimal128 ldexpd128(_Decimal128 x, int exp);
10
            long int llogbd32( Decimal32 x);
            long int llogbd64( Decimal64 x);
           long int llogbd128( Decimal128 x);
            Decimal32 logd32( Decimal32 x);
            Decimal64 logd64(_Decimal64 x);
15
            Decimal128 logd128 ( Decimal128 x);
            Decimal32 log10d32( Decimal32 x);
            Decimal64 log10d64( Decimal64 x);
20
            Decimal128 log10d128 ( Decimal128 x);
            _Decimal32 log1pd32(_Decimal32 x);
            _Decimal64 log1pd64(_Decimal64 x);
           _Decimal128 log1pd128(_Decimal128 x);
25
            _Decimal32 log2d32(_Decimal32 x);
            Decimal64 log2d64( Decimal64 x);
           Decimal128 log2d128 (Decimal128 x);
30
            Decimal32 logbd32( Decimal32 x);
            Decimal64 logbd64( Decimal64 x);
           Decimal128 logbd128 ( Decimal128 x);
            _Decimal32 modfd32(_Decimal32 value, _Decimal32 *iptr);
35
            _Decimal64 modfd64(_Decimal64 value, _Decimal64 *iptr);
           Decimal128 modfd128 ( Decimal128 value, Decimal128 *iptr);
            _Decimal32 scalbnd32(_Decimal32 x, int n);
            Decimal64 scalbnd64( Decimal64 x, int n);
40
            Decimal128 scalbnd128( Decimal128 x, int n);
            _Decimal32 scalblnd32(_Decimal32 x, long int n);
             Decimal64 scalblnd64( Decimal64 x, long int n);
           _Decimal128 scalblnd128(_Decimal128 x, long int n);
       7.12.7 Power and absolute-value functions
45
            Decimal32 cbrtd32( Decimal32 x);
            Decimal64 cbrtd64( Decimal64 x);
           Decimal128 cbrtd128 ( Decimal128 x);
50
            Decimal32 fabsd32( Decimal32 x);
            Decimal64 fabsd64( Decimal64 x);
            _Decimal128 fabsd128(_Decimal128 x);
            _Decimal32 hypotd32(_Decimal32 x, _Decimal32 y);
            Decimal64 hypotd64(_Decimal64 x, _Decimal64 y);
55
            _Decimal128 hypotd128(_Decimal128 x, _Decimal128 y);
```

_Decimal32 powd32(_Decimal32 x, _Decimal32 y); Decimal64 powd64(_Decimal64 x, _Decimal64 y); _Decimal128 powd128(_Decimal128 x, _Decimal128 y); 5 _Decimal32 sqrtd32(_Decimal32 x); Decimal64 sqrtd64(Decimal64 x); Decimal128 sqrtd128 (Decimal128 x); 7.12.8 Error and gamma functions Decimal32 erfd32(Decimal32 x); 10 Decimal64 erfd64(Decimal64 x); Decimal128 erfd128 (_Decimal128 x); Decimal32 erfcd32(Decimal32 x); Decimal64 erfcd64(Decimal64 x); 15 Decimal128 erfcd128 (Decimal128 x); _Decimal32 lgammad32(_Decimal32 x); _Decimal64 lgammad64(_Decimal64 x); Decimal128 lgammad128 (Decimal128 x); 20 _Decimal32 tgammad32(_Decimal32 x); Decimal64 tgammad64 (Decimal64 x); Decimal128 tgammad128 (Decimal128 x); 7.12.9 Nearest integer functions 25 Decimal32 ceild32(Decimal32 x); Decimal64 ceild64(Decimal64 x); Decimal128 ceild128 (Decimal128 x); Decimal32 floord32(Decimal32 x); Decimal64 floord64(Decimal64 x); 30 _Decimal128 floord128(_Decimal128 x); _Decimal32 nearbyintd32(_Decimal32 x); _Decimal64 nearbyintd64(_Decimal64 x); 35 _Decimal128 nearbyintd128(_Decimal128 x); _Decimal32 rintd32(_Decimal32 x); _Decimal64 rintd64(_Decimal64 x); Decimal128 rintd128 (Decimal128 x); 40 long int lrintd32(Decimal32 x); long int lrintd64(Decimal64 x); long int lrintd128(Decimal128 x); 45 long long int llrintd32(Decimal32 x); long long int llrintd64(Decimal64 x); long long int llrintd128(Decimal128 x); Decimal32 roundd32(Decimal32 x); 50 Decimal64 roundd64(Decimal64 x); Decimal128 roundd128 (Decimal128 x); long int lroundd32(_Decimal32 x); long int lroundd64(_Decimal64 x); 55 long int lroundd128(_Decimal128 x);

```
long long int llroundd64( Decimal64 x);
           long long int llroundd32(_Decimal32 x);
           long long int llroundd128(_Decimal128 x);
5
           _Decimal32 roundevend32(_Decimal32 x);
           Decimal64 roundevend64(Decimal64 x);
           Decimal128 roundevend128 ( Decimal128 x);
            Decimal32 truncd32( Decimal32 x);
10
            Decimal64 truncd64( Decimal64 x);
           Decimal128 truncd128 ( Decimal128 x);
           intmax t fromfpd32( Decimal32 x, int round, unsigned int width);
           intmax t fromfpd64( Decimal64 x, int round, unsigned int width);
15
           intmax t fromfpd128 ( Decimal128 x, int round, unsigned int width);
           uintmax t ufromfpd32( Decimal32 x, int round, unsigned int width);
           uintmax t ufromfpd64( Decimal64 x, int round, unsigned int width);
           uintmax t ufromfpd128 (Decimal128 x, int round, unsigned int width);
20
           intmax_t fromfpxd32(_Decimal32 x, int round, unsigned int width);
           intmax_t fromfpxd64(_Decimal64 x, int round, unsigned int width);
           intmax_t fromfpxd128(_Decimal128 x, int round, unsigned int width);
           uintmax_t ufromfpxd32(_Decimal32 x, int round, unsigned int width);
           uintmax_t ufromfpxd64(_Decimal64 x, int round, unsigned int width);
25
           uintmax_t ufromfpxd128(_Decimal128 x, int round, unsigned int width);
       7.12.10 Remainder functions
            _Decimal32 fmodd32(_Decimal32 x, _Decimal32 y);
            Decimal64 fmodd64 ( Decimal64 x, Decimal64 y);
           _Decimal128 fmodd128(_Decimal128 x, _Decimal128 y);
30
            _Decimal32 remainderd32(_Decimal32 x, _Decimal32 y);
            Decimal64 remainderd64(_Decimal64 x, _Decimal64 y);
           Decimal128 remainderd128 ( Decimal128 x, Decimal128 y);
       7.12.11 Manipulation functions
35
            _Decimal32 copysignd32(_Decimal32 x, _Decimal32 y);
            Decimal64 copysignd64 (_Decimal64 x, _Decimal64 y);
           _Decimal128 copysignd128(_Decimal128 x, _Decimal128 y);
            Decimal32 nand32(const char *tagp);
40
            Decimal64 nand64(const char *tagp);
           Decimal128 nand128(const char *tagp);
            Decimal32 nextafterd32 ( Decimal32 x, Decimal32 y);
            _Decimal64 nextafterd64(_Decimal64 x, _Decimal64 y);
           Decimal128 nextafterd128 (Decimal128 x, Decimal128 y);
45
            Decimal32 nexttowardd32( Decimal32 x, Decimal128 y);
            Decimal64 nexttowardd64(_Decimal64 x, _Decimal128 y);
           _Decimal128 nexttowardd128(_Decimal128 x, _Decimal128 y);
50
           _Decimal32 nextupd32(_Decimal32 x);
            Decimal64 nextupd64( Decimal64 x);
           Decimal128 nextupd128 ( Decimal128 x);
```

```
_Decimal32 nextdownd32(_Decimal32 x);
             Decimal64 nextdownd64(_Decimal64 x);
            _Decimal128 nextdownd128(_Decimal128 x);
            int canonicalized32(_Decimal32 * cx, const _Decimal32 * x);
5
            int canonicalized64(_Decimal64 * cx, const _Decimal64 * x);
            int canonicalized128( Decimal128 * cx, const Decimal128 * x);
        7.12.12 Maximum, minimum, and positive difference functions
            Decimal32 fdimd32( Decimal32 x, Decimal32 y);
10
             Decimal64 fdimd64(_Decimal64 x, _Decimal64 y);
            Decimal128 fdimd128(_Decimal128 x, _Decimal128 y);
            _Decimal32 fmaxd32(_Decimal32 x, _Decimal32 y);
             Decimal64 fmaxd64(_Decimal64 x, _Decimal64 y);
15
            _Decimal128 fmaxd128(_Decimal128 x, _Decimal128 y);
            _Decimal32 fmind32(_Decimal32 x, _Decimal32 y);
             Decimal64 fmind64(_Decimal64 x, _Decimal64 y);
            _Decimal128 fmind128(_Decimal128 x, _Decimal128 y);
20
            _Decimal32 fmaxmagd32(_Decimal32 x, _Decimal32 y);
            Decimal64 fmaxmagd64(_Decimal64 x, _Decimal64 y);
            Decimal128 fmaxmagd128 (Decimal128 x, Decimal128 y);
25
            _Decimal32 fminmagd32(_Decimal32 x, _Decimal32 y);
            Decimal64 fminmagd64 (Decimal64 x, Decimal64 y);
            Decimal128 fminmagd128 (Decimal128 x, Decimal128 y);
        7.12.13 Floating multiply-add
            _Decimal32 fmad32(_Decimal32 x, _Decimal32 y, _Decimal32 z);
30
             Decimal64 fmad64(_Decimal64 x, _Decimal64 y, _
                                                             Decimal64 z);
            _Decimal128 fmad128(_Decimal128 x, _Decimal128 y, _Decimal128 z);
        7.12.13a Functions that round result to narrower format
             Decimal32 d32addd64( Decimal64 x, Decimal64 y);
             Decimal32 d32addd128(_Decimal128 x, _Decimal128 y);
35
            Decimal64 d64addd128 (Decimal128 x, Decimal128 y);
            _Decimal32 d32subd64(_Decimal64 x, _Decimal64 y);
            Decimal32 d32subd128(_Decimal128 x, _Decimal128 y);
            Decimal64 d64addd128( Decimal128 x, Decimal128 y);
40
            _Decimal32 d32muld64(_Decimal64 x, _Decimal64 y);
            _Decimal32 d32muld128(_Decimal128 x, _Decimal128 y);
_Decimal64 d64muld128(_Decimal128 x, _Decimal128 y);
            _Decimal32 d32divd64(_Decimal64 x, _Decimal64 y);
45
             Decimal32 d32divd128(_Decimal128 x, _Decimal128 y);
            _Decimal64 d64divd128(_Decimal128 x, _Decimal128 y);
            _Decimal32 d32fmad64(_Decimal64 x, _Decimal64 y, _Decimal64 z);
50
            _Decimal32 d32fmad128(_Decimal128 x, _Decimal128 y, _Decimal128 z);
            _Decimal64 d64fmad128(_Decimal128 x, _Decimal128 y, _Decimal128 z);
```

```
Decimal32 d32sqrtd64( Decimal64 x);
            Decimal32 d32sqrtd128(_Decimal128 x);
            Decimal64 d64sqrtd128( Decimal128 x);
       F.10.12 Total order functions
5
           int totalorderd32( Decimal32 x, Decimal32 y);
           int totalorderd64( Decimal64 x, Decimal64 y);
           int totalorderd128( Decimal128 x, Decimal128 y);
           int totalordermagd32( Decimal32 x, Decimal32 y);
10
           int totalordermagd64(_Decimal64 x, _Decimal64 y);
           int totalordermagd128( Decimal128 x, Decimal128 y);
       F.10.13 Payload functions
            Decimal32 getpayloadd32(const _Decimal32 *x);
            Decimal64 getpayloadd64(const Decimal64 *x);
15
            Decimal128 getpayloadd128 (const Decimal128 *x);
            int setpayloadd32(_Decimal32 *res, _Decimal32 pl);
            int setpayloadd64(_Decimal64 *res, _Decimal64 pl);
20
           int setpayloadd128(_Decimal128 *res, _Decimal128 pl);
```

```
int setpayloadsigd32(_Decimal32 *res, _Decimal32 pl);
int setpayloadsigd64(_Decimal64 *res, _Decimal64 pl);
int setpayloadsigd128(_Decimal128 *res, _Decimal128 pl);
```

25 In 7.12.10.3, attach a footnote to the heading:

7.12.10.3 The remquo functions

where the footnote is:

*) There are no decimal floating-point versions of the **remquo** functions.

Add to the end of 7.12.14#1:

30 [1] ... If either argument has decimal floating type, the other argument shall have decimal floating type as well.

Replace 7.12.6.4 paragraphs 2 and 3:

[2] The **frexp** functions break a floating-point number into a normalized fraction and an integral power of 2. They store the integer in the **int** object pointed to by **exp**.

35 [3] If value is not a floating-point number or if the integral power of 2 is outside the range of int, the results are unspecified. Otherwise, the frexp functions return the value x, such that x has a magnitude in the interval [1/2, 1) or zero, and value equals x × 2^{*exp}. If value is zero, both parts of the result are zero.

with the following:

40 [2] The **frexp** functions break a floating-point number into a normalized fraction and an integer exponent. They store the integer in the **int** object pointed to by **exp**. If the type of the function is a standard floating type, the exponent is an integral power of 2. If the type of the function is a decimal floating type, the exponent is an integral power of 10.

[3] If value is not a floating-point number or the integral power is outside the range of int, the results are unspecified. Otherwise, the frexp functions return the value x, such that: x has a magnitude in the interval [1/2, 1) or zero, and value equals $x \times 2^{*exp}$, when the type of the function is a standard floating type; or x has a magnitude in the interval [1/10, 1) or zero, and value equals $x \times 10^{*exp}$, when the type of the function is a decimal floating type. If value is zero, both parts of the result are zero.

Replace 7.12.6.6 paragraphs 2 and 3:

[2] The **ldexp** functions multiply a floating-point number by an integral power of 2. A range error may occur.

10 [3] The **ldexp** functions return $\mathbf{x} \times 2^{exp}$.

with the following:

[2] The **ldexp** functions multiply a floating-point number by an integral power of 2 when the type of the function is a standard floating type, or by an integral power of 10 when the type of the function is a decimal floating type. A range error may occur.

15 [3] The ldexp functions return $\mathbf{x} \times 2^{exp}$ when the type of the function is a standard floating type, or return $\mathbf{x} \times 10^{exp}$ when the type of the function is a decimal floating type.

Replace 7.12.6.11#2:

[2] The logb functions extract the exponent of \mathbf{x} , as a signed integer value in floating-point format. If \mathbf{x} is subnormal it is treated as though it were normalized; thus, for positive finite \mathbf{x} ,

20
$$1 \le \mathbf{x} \times \mathbf{FLT} \ \mathbf{RADIX}^{-\log b(\mathbf{x})} < \mathbf{FLT} \ \mathbf{RADIX}$$

A domain error or pole error may occur if the argument is zero.

with the following:

[2] The logb functions extract the exponent of \mathbf{x} , as a signed integer value in floating-point format. If \mathbf{x} is subnormal it is treated as though it were normalized; thus, for positive finite \mathbf{x} ,

$1 \le \mathbf{x} \times b^{-\log b(\mathbf{x})} < b$

where $b = FLT_RADIX$ if the type of the function is a standard floating type, or b = 10 if the type of the function is a decimal floating type. A domain error or range error may occur if the argument is zero.

Replace 7.12.6.13 paragraphs 2 and 3:

[2] The scalbn and scalbln functions compute $x \times FLT_RADIX^n$ efficiently, not normally by computing FLT_RADIX^n explicitly. A range error may occur.

[3] The scalbn and scalbln functions return $\mathbf{x} \times \mathbf{FLT}$ RADIXⁿ.

with the following:

35

[2] The scalbn and scalbln functions compute $\mathbf{x} \times b^n$, where $b = \text{FLT}_RADIX$ if the type of the function is a standard floating type, or b = 10 if the type of the function is a decimal floating type. A range error may occur.

[3] The scalbn and scalbln functions return $\mathbf{x} \times b^{n}$.

12.4 Decimal-only functions in <math.h>

This clause adds new functions to <math.h>.

12.4.1 Quantum and quantum exponent functions

This specification does not carry forward the quantexpdN functions from TR 24732, which return the quantum exponent of their argument as an int. Instead it introduces the quantumdN functions, which return the quantum rather than the quantum exponent, and the llquantexpdN functions, which return the quantum exponent as a long long int, instead of int. The new interfaces offer natural extensions for support of wider IEC 60559 decimal formats in Part 3 of Technical Specification 18661.

Change to C11 + TS18661-1:

10 After subclause 7.12.11, add a new subclause:

7.12.11a Quantum and quantum exponent functions

7.12.11a.1 The quantized N functions

Synopsis

```
[1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
    _Decimal32 quantized32(_Decimal32 x, _Decimal32 y);
    _Decimal64 quantized64(_Decimal64 x, _Decimal64 y);
    _Decimal128 quantized128(_Decimal128 x, _Decimal128 y);
```

20 Description

15

25

[2] The quantizedN functions compute, if possible, a value with the numerical value of \mathbf{x} and the quantum exponent of \mathbf{y} . If the quantum exponent is being increased, the value shall be correctly rounded; if the result does not have the same value as \mathbf{x} , the "inexact" floating-point exception shall be raised. If the quantum exponent is being decreased and the significand of the result has more digits than the type would allow, the result is NaN and a domain error occurs. If one or both operands are NaN the result is NaN. Otherwise if only one operand is infinite, the result is NaN and a domain error occurs. If both operands are infinite, the result is DEC_INFINITY with the sign of \mathbf{x} , converted to the type of the function. The quantize functions do not raise the "underflow" floating-point exception.

30 Returns

[3] The quantized N functions return a value with the numerical value of \mathbf{x} (except for any rounding) and the quantum exponent of \mathbf{y} .

7.12.11a.2 The samequantumd N functions

Synopsis

```
35 [1] #define __STDC_WANT_IEC_60559_DFP_EXT_____
#include <math.h>
__Bool samequantumd32(_Decimal32 x, __Decimal32 y);
__Bool samequantumd64(_Decimal64 x, __Decimal64 y);
__Bool samequantumd128(_Decimal128 x, __Decimal128 y);
40
```

Description

[2] The same quantum dN functions determine if the quantum exponents of x and y are the same. If both x and y are NaN, or both infinite, they have the same quantum exponents; if exactly one operand is infinite or exactly one operand is NaN, they do not have the same quantum exponents. The samequantumdN functions raise no floating-point exception.

Returns

[3] The same quantum N functions return nonzero (true) when x and y have the same quantum exponents, zero (false) otherwise.

7.12.11a.3 The quantumd N functions

10 **Synopsis**

5

15

```
[1] #define STDC WANT IEC 60559 DFP EXT
   #include <math.h>
   Decimal32 quantumd32( Decimal32 x);
    Decimal64 quantumd64( Decimal64 x);
   Decimal128 quantumd128 (Decimal128 x);
```

Description

[2] The quantumdN functions compute the quantum (5.2.4.2.2a) of a finite argument. If x is infinite, the result is $+\infty$. If x is NaN, the result is NaN.

20 Returns

[3] The guantumdN functions return the guantum of \mathbf{x} .

7.12.11a.4 The llquantexpdN functions

Synopsis

```
25
```

[1] #define __STDC_WANT_IEC_60559_DFP_EXT__ #include <math.h> long long int llquantexpd32(Decimal32 x); long long int llquantexpd64(Decimal64 x); long long int llquantexpd128(Decimal128 x);

30 Description

[2] The **llquantexpd** functions compute the quantum exponent (5.2.4.2.2a) of a finite argument. If x is infinite or NaN, they compute **LLONG MIN** and a domain error occurs.

Returns

[3] The llquantexpdN functions return the quantum exponent of x.

35 12.4.2 Decimal re-encoding functions

IEC 60559 defines two alternative encoding schemes for its decimal interchange formats: one based on decimal encoding of the significand, the other based on binary encoding of the significand. (See IEC 60559 for details.) The two encoding schemes encode the same values. The re-encoding functions in this subclause allow the user to convert data, in either of the encoding schemes, to and from values of the corresponding decimal floating type.

Change to C11 + TS18661-1:

After subclause 7.12.11a, add a new subclause:

7.12.11b Decimal re-encoding functions

7.12.11b.1 The encodedecdN functions

```
5 Synopsis
```

10

20

[1] #define __STDC_WANT_IEC_60559_DFP_EXT__ #include <math.h> void encodedecd32(unsigned char * restrict encptr, const _Decimal32 * restrict xptr); void encodedecd64(unsigned char * restrict encptr, const _Decimal64 * restrict xptr); void encodedecd128(unsigned char * restrict encptr, const _Decimal128 * restrict xptr);

15 **Description**

[2] The encodedecdN functions convert *xptr into an IEC 60559 decimalN encoding in the encoding scheme based on decimal encoding of the significand and store the resulting encoding as an N/8 element array, with 8 bits per array element, in the object pointed to by encptr. The order of bytes in the array is implementation-defined. These functions preserve the value of *xptr and raise no floating-point exceptions. If *xptr is non-canonical, these functions may or may not produce a canonical encoding.

Returns

[3] The **encodedecd***N* functions return no value.

7.12.11b.2 The decodedecd N functions

Synopsis

```
25 [1] #define __STDC_WANT_IEC_60559_DFP_EXT__
#include <math.h>
void decodedecd32(_Decimal32 * restrict xptr, const unsigned char *
restrict encptr);
void decodedecd64(_Decimal64 * restrict xptr, const unsigned char *
30 restrict encptr);
void decodedecd128(_Decimal128 * restrict xptr, const unsigned char *
restrict encptr);
```

Description

[2] The decodedecdN functions interpret the N/8 element array pointed to by encptr as an IEC 60559 decimalN encoding, with 8 bits per array element, in the encoding scheme based on decimal encoding of the significand. The order of bytes in the array is implementation-defined. These functions convert the given encoding into a value of type _DecimalN, and store the result in the object pointed to by xptr. These functions preserve the encoded value and raise no floating-point exceptions. If the encoding is non-canonical, these functions may or may not produce a canonical representation.

Returns

[3] The decodedecd*N* functions return no value.

7.12.11b.3 The encodebind N functions

Synopsis

	[1]	<pre>#defineSTDC_WANT_IEC_60559_DFP_EXT</pre>
		<pre>#include <math.h></math.h></pre>
5		<pre>void encodebind32(unsigned char * restrict encptr, const _Decimal32 * restrict xptr);</pre>
		<pre>void encodebind64(unsigned char * restrict encptr, const _Decimal64 * restrict xptr);</pre>
		void encodebind128(unsigned char * restrict encptr, const Decimal128 *
10		restrict xptr);

Description

15

25

30

35

[2] The encodebind N functions convert *xptr into an IEC 60559 decimal N encoding in the encoding scheme based on binary encoding of the significand and store the resulting encoding as an N/8 element array, with 8 bits per array element, in the object pointed to by encptr. The order of bytes in the array is implementation-defined. These functions preserve the value of *xptr and raise no floating-point exceptions. If *xptr is non-canonical, these functions may or may not produce a canonical encoding.

Returns

[3] The encodebindN functions return no value.

20 7.12.11b.4 The decodebind N functions

Synopsis

[1]	<pre>#defineSTDC_WANT_IEC_60559_DFP_EXT</pre>
	<pre>#include <math.h></math.h></pre>
	<pre>void decodebind32(_Decimal32 * restrict xptr, const unsigned char *</pre>
	restrict encptr);
	<pre>void decodebind64(_Decimal64 * restrict xptr, const unsigned char *</pre>
	restrict encptr);
	<pre>void decodebind128(_Decimal128 * restrict xptr, const unsigned char</pre>
	restrict encptr);

Description

[2] The decodebindN functions interpret the N/8 element array pointed to by encptr as an IEC 60559 decimalN encoding, with 8 bits per array element, in the encoding scheme based on binary encoding of the significand. The order of bytes in the array is implementation-defined. These functions convert the given encoding into a value of type __DecimalN, and store the result in the object pointed to by xptr. These functions preserve the encoded value and raise no floating-point exceptions. If the encoding is non-canonical, these functions may or may not produce a canonical representation.

Returns

[3] The decodebindN functions return no value.

40 12.5 Formatted input/output specifiers

With the following decimal forms of the a (or A), format specifier, the printf family of functions provide conversions to decimal character sequences that preserve quantum exponents, as required by IEC 60559.

*

Changes to C11 + TS18661-1:

5

15

Add the following to 7.21.6.1#7, 7.21.6.2#11, 7.29.2.1#7, and 7.29.2.2#11:

- H Specifies that a following a, A, e, E, f, F, g, or G conversion specifier applies to a _Decimal32 argument.
- D Specifies that a following a, A, e, E, f, F, g, or G conversion specifier applies to a _Decimal64 argument.
 - DD Specifies that a following a, A, e, E, f, F, g, or G conversion specifier applies to a _Decimal128 argument.

Add the following to 7.21.6.1#8 and 7.29.2.1#8, under a,A conversion specifiers:

- 10 If an \mathbf{H} , \mathbf{D} , or $\mathbf{D}\mathbf{D}$ modifier is present and the precision is missing, then for a decimal floating type argument represented by a triple of integers (*s*, *c*, *q*), where *n* is the number of digits in the coefficient *c*,
 - if $-(n+5) \le q \le 0$, use style **f** formatting with formatting precision equal to -q,
 - otherwise, use style **e** formatting with formatting precision equal to n 1, with the exceptions that if c = 0 then the *digit-sequence* in the *exponent-part* shall have the value q (rather than 0), and that the exponent is always expressed with the minimum number of digits required to represent its value (the exponent never contains a leading zero).
- If the precision is present (in the conversion specification) and is zero or at least as large as the precision *p* (5.2.4.2.2) of the decimal floating type, the conversion is as if the precision were missing. If the precision is present (and nonzero) and less than the precision *p* of the decimal floating type, the conversion first obtains an intermediate result by rounding the input in the type, according to the current rounding direction for decimal floating-point operations, to the number of digits specified by the precision, then converts the intermediate result as if the precision were missing. The length of the coefficient of the intermediate result is the smallest number, at least as large as the formatting precision, for which the quantum exponent is within the quantum exponent range of the type (see 5.2.4.2.2a). The intermediate rounding may overflow.

EXAMPLE 1 Following are representations of <u>Decimal64</u> arguments as triples (s, c, q) and the corresponding character sequences printf produces with %Da:

	(1, 123, 0)	123	
30	(-1, 123, 0)	-123	
	(1, 123, -2)	1.23	
	(1, 123, 1)	1.23e+3	
	(-1, 123, 1)	-1.23e+3	
	(1, 123, -8)	0.0000123	3
35	(1, 123, -9)	1.23e-7	
	(1, 120, -8)	0.0000120)
	(1, 120, -9)	1.20e-7	
	(1, 12345678901	23456, 0)	1234567890123456
	(1, 12345678901	23456, 1)	1.234567890123456e+16
40	(1, 12345678901	23456, -1)	123456789012345.6
	(1, 12345678901	23456, -21)	0.000001234567890123456
	(1, 12345678901	23456, -22)	1.234567890123456e-7
	(1,0,0)	0	
	(-1, 0, 0)	-0	
45	(1,0,-6)	0.00000	
	(1,0,-7)	0e-7	

0e+2
0.00005
0.000050
5e-7

5

EXAMPLE 2 To illustrate the effects of a precision specification, the sequence:

```
_Decimal32 x = 6543.00DF; // represented by the triple (1, 654300, -2)
           printf("%Ha\n", x);
           printf("%.6Ha\n", x);
10
           printf("%.5Ha\n", x);
           printf("%.4Han'', x);
           printf("%.3Ha\n", x);
           printf("%.2Ha\n", x);
           printf("%.1Ha\n", x);
```

15 printf("%.0Ha\n", x);

assuming default rounding, results in:

6543.00
6543.00
6543.0
6543
6.54e+3
6.5e+3
7e+3
6543.00

EXAMPLE 3 To illustrate the effects of the exponent range, the sequence:

```
Decimal32 x = 9543210e87DF; // represented by the triple (1, 9543210, 87)
            Decimal32 y = 9500000e90DF; // represented by the triple (1, 9500000, 90)
30
           printf("%.6Ha\n", x);
           printf("%.5Ha\n", x);
           printf("%.4Ha\n", x);
           printf("%.3Ha\n", x);
           printf("%.2Ha\n", x);
35
           printf("%.1Ha\n", x);
           printf("%.1Ha\n", y);
```

assuming default rounding, results in:

```
9.54321e+93
40
            9.5432e+93
            9.543e+93
            9.540e+93
            9.500e+93
            1.0000e+94
            inf
```

```
45
```

12.6 strtod/ functions in <stdlib.h>

The specifications of these functions are similar to those of strtod, strtof, and strtold as defined in C11 7.22.1.3. These functions are declared in <stdlib.h>.

Changes to C11 + TS18661-1:

After 7.22.1.3, add:

7.22.1.3a The strtodN functions

Synopsis

5

10

30

35

[1] #define __STDC_WANT_IEC_60559_DFP_EXT__ #include <stdlib.h> __Decimal32 strtod32(const char * restrict nptr, char ** restrict endptr); __Decimal64 strtod64(const char * restrict nptr, char ** restrict endptr); __Decimal128 strtod128(const char * restrict nptr, char ** restrict endptr);

Description

15 [2] The strtodN functions convert the initial portion of the string pointed to by nptr to _DecimaldN representation. First, they decompose the input string into three parts: an initial, possibly empty, sequence of white-space characters (as specified by the isspace function); a subject sequence resembling a floating constant or representing an infinity or NaN; and a final string of one or more unrecognized characters, including the terminating null character of the input string. Then, they attempt to convert the subject sequence to a floating-point number, and return the result.

[3] The expected form of the subject sequence is an optional plus or minus sign, then one of the following:

- a nonempty sequence of decimal digits optionally containing a decimal-point character, then an optional exponent part as defined in 6.4.4.2
- 25 INF OR INFINITY, ignoring case
 - **NAN** or **NAN**(*d*-*char*-*sequence*_{opt}), ignoring case in the **NAN** part, where:

d-char-sequence: digit nondigit d-char-sequence digit d-char-sequence nondigit

The subject sequence is defined as the longest initial subsequence of the input string, starting with the first non-white-space character, that is of the expected form. The subject sequence contains no characters if the input string is not of the expected form.

[4] If the subject sequence has the expected form for a floating-point number, the sequence of characters starting with the first digit or the decimal-point character (whichever occurs first) is interpreted as a floating constant according to the rules of 6.4.4.2, except that it is not a hexadecimal floating number, that the decimal-point character is used in place of a period, and that if neither an exponent part nor a decimal-point character appears in a decimal floating-point number, an exponent part of the appropriate type with value zero is assumed to follow the last digit in the string. If the subject sequence begins with a minus sign, the sequence is interpreted as an infinity. A character sequence **INF** or **INFINITY** is interpreted as an infinity. A character sequence is implementation-defined. A pointer to the final string is stored in the object pointed to by endptr, provided that endptr is not a null pointer.

[5] If the sequence is negated, the sign *s* is set to -1, else *s* is set to 1.

5

10

15

[6] If the subject sequence has the expected form for a floating-point number, then the result shall be correctly rounded as specified in IEC 60559.

[7] The coefficient c and the quantum exponent q of a finite converted floating-point number are determined from the subject sequence as follows:

- The fractional-constant or digit-sequence and the exponent-part (if any) are extracted from the subject sequence. If there is an exponent-part, then q is set to the value of sign_{opt} digitsequence in the exponent-part. If there is no exponent-part, q is set to 0.
 - If there is a *fractional-constant*, q is decreased by the number of digits to the right of the decimal point and the decimal point is removed to form a *digit-sequence*.
- *c* is set to the value of the *digit-sequence* (after any decimal point has been removed).
 - Rounding required because of insufficient precision or range in the type of the result will round *c* to the full precision available in the type, and will adjust *q* accordingly within the limits of the type, provided the rounding does not yield an infinity (in which case an appropriately signed internal representation of infinity is returned). If the full precision of the type would require *q* to be smaller than the minimum for the type, then *q* is pinned at the minimum and *c* is adjusted through the subnormal range accordingly, perhaps to zero.

EXAMPLE Following are subject sequences of the decimal form and the resulting triples (s, c, q) produced by strtod64. Note that for _Decimal64, the precision (maximum coefficient length) is 16 and the quantum exponent range is $-398 \le q \le 369$.

20	"0" "0.00"	(1,0,0)
	"0.00"	(1,0,-2)
	"123" "-123"	(1,123,0)
	"1.23E3"	(−1,123,0) (1,123,1)
25	"1.23E5 "1.23E+3"	(1,123,1)
25	"12.3E+7"	(1,123,1)
	"12.0"	(1,120,-1)
	"12.3"	(1,123,-1)
	"0.00123"	(1,123,-5)
30	"-1.23E-12"	(-1,123,-14)
50	"1234.5E-4"	(1,123, 14)
	"-0"	(-1,0,0)
	"-0.00"	(-1,0,-2)
	"0E+7"	(1,0,7)
35	"-0E-7"	(-1,0,-7)
	"1234567890123	
		ing on rounding mode
	"1234E-400"	(1, 12, −398) or (1, 13, −398) depending on rounding mode
	"1234E-402"	(1, 0, -398) or $(1, 1, -398)$ depending on rounding mode
40	"1000."	(1,1000,0)
	".0001"	(1,1,-4)
	"1000.e0"	(1,1000,0)
	".0001e0"	(1,1,-4)
	"1000.0"	(1,10000,-1)
45	"0.0001"	(1,1,-4)
	"1000.00"	(1,100000,-2)
	"00.0001"	(1,1,-4)
	"001000."	(1,1000,0)
	"001000.0"	(1,10000,-1)
50	"001000.00"	(1,100000,-2)
	"00.00"	(1,0,-2)
	"00."	(1,0,0)
	".00"	(1,0,-2)

"00.00e-5"	(1,0,-7)
"00.e-5"	(1,0,-5)
".00e-5"	(1,0,-7)
"0x1.8p+4"	(1,0,0), and a pointer to "x1.8p+4" is stored in the object pointed to by endptr,
	provided endptr is not a null pointer
"infinite"	infinity, and a pointer to "inite" is stored in the object pointed to by endptr,
	provided endptr is not a null pointer

[8] In other than the "C" locale, additional locale-specific subject sequence forms may be accepted.

10 [9] If the subject sequence is empty or does not have the expected form, no conversion is performed; the value of nptr is stored in the object pointed to by endptr, provided that endptr is not a null pointer.

Returns

5

[10] The functions return the correctly rounded converted value, if any. If no conversion could be performed, the value of the triple (1,0,0) is returned. If the correct value overflows, the value of the macro **ERANGE** is stored in **errno**. If the result underflows (7.12.1), whether **errno** acquires the value **ERANGE** is implementation-defined.

In 7.22.1.3a#4, attach a footnote to the wording:

the meaning of the d-char sequence is implementation-defined.

20 where the footnote is:

*) An implementation may use the d-char sequence to determine extra information to be represented in the NaN's significand.

12.7 wcstod/ functions in <wchar.h>

The specifications of these functions are similar to those of wcstod, wcstof, and wcstold as defined in C11 7.29.4.1.1. They are declared in <wchar.h>.

Change to C11 + TS18661-1:

After 7.29.4.1.1, add:

7.29.4.1.1a The wcstod N functions

Synopsis

```
30 [1] #define __STDC_WANT_IEC_60559_DFP_EXT__
```

```
#include <wchar.h>
    _Decimal32 wcstod32(const wchar_t * restrict nptr, wchar_t ** restrict
      endptr);
    _Decimal64 wcstod64(const wchar_t * restrict nptr, wchar_t ** restrict
      endptr);
    _Decimal128 wcstod128(const wchar_t * restrict nptr, wchar_t **
      restrict endptr);
```

Description

one or more unrecognized wide characters, including the terminating null wide character of the input wide string. Then, they attempt to convert the subject sequence to a floating-point number, and return the result.

[3] The expected form of the subject sequence is an optional plus or minus sign, then one of the following:

- a nonempty sequence of decimal digits optionally containing a decimal-point wide character, then an optional exponent part as defined in 6.4.4.2;
- INF or INFINITY, ignoring case
- **NAN** or **NAN**(*d*-*wchar*-*sequence*_{opt}), ignoring case in the **NAN** part, where:
- 10 *d-wchar-sequence: digit nondigit d-wchar-sequence digit d-wchar-sequence nondigit*

15

5

The subject sequence is defined as the longest initial subsequence of the input wide string, starting with the first non-white-space wide character, that is of the expected form. The subject sequence contains no wide characters if the input wide string is not of the expected form.

- [4] If the subject sequence has the expected form for a floating-point number, the sequence of wide characters starting with the first digit or the decimal-point wide character (whichever occurs first) is interpreted as a floating constant according to the rules of 6.4.4.2, except that it is not a hexadecimal floating number, that the decimal-point wide character is used in place of a period, and that if neither an exponent part nor a decimal-point wide character appears in a decimal floating-point number, an exponent part of the appropriate type with value zero is assumed to follow the last digit in the string. If the subject sequence begins with a minus sign, the sequence is interpreted as negated (before rounding). A wide character sequence INF or INFINITY is interpreted as an infinity. A wide character sequence is implementation-defined. A pointer to the final wide string is stored in the object pointed to by endptr, provided that endptr is not a null pointer.
- 30 [5] If the sequence is negated, the sign *s* is set to -1, else *s* is set to 1.

[6] If the subject sequence has the expected form for a floating-point number, then the result shall be correctly rounded as specified in IEC 60559.

[7] The coefficient c and the quantum exponent q of a finite converted floating-point number are determined from the subject sequence as follows:

- The fractional-constant or digit-sequence and the exponent-part (if any) are extracted from the subject sequence. If there is an exponent-part, then q is set to the value of signout digitsequence in the exponent-part. If there is no exponent-part, q is set to 0.
- If there is a *fractional-constant*, g is decreased by the number of digits to the right of the decimal point and the decimal point is removed to form a *digit-sequence*.
- c is set to the value of the *digit-sequence* (after any decimal point has been removed).
- Rounding required because of insufficient precision or range in the type of the result will round c to the full precision available in the type, and will adjust q accordingly within the limits of the type, provided the rounding does not yield an infinity (in which case an appropriately signed internal representation of infinity is returned). If the full precision of the type would require q to be smaller than the minimum for the type, then q is pinned at the minimum and c is adjusted through the subnormal range accordingly, perhaps to zero.
- [8] In other than the "C" locale, additional locale-specific subject sequence forms may be accepted. 15

[9] If the subject sequence is empty or does not have the expected form, no conversion is performed; the value of nptr is stored in the object pointed to by endptr, provided that endptr is not a null pointer.

Returns

5

10

- [10] The functions return the converted value, if any. If no conversion could be performed, the value 20 of the triple (1,0,0) is returned. If the correct value overflows and default rounding is in effect (7.12.1), plus or minus HUGE VAL D32, HUGE VAL D64, or HUGE VAL D128 is returned (according to the return type and sign of the value), and the value of the macro ERANGE is stored in errno. If the result underflows (7.12.1), the functions return a value whose magnitude is no greater than the smallest 25 normalized positive number in the return type; whether errno acquires the value ERANGE is implementation-defined.
 - In 7.29.4.1.3#4, attach a footnote to the wording:

the meaning of the d-wchar sequence is implementation-defined.

where the footnote is:

30 *) An implementation may use the d-wchar sequence to determine extra information to be represented in the NaN's significand.

12.8 strfromdN functions in <stdlib.h>

The specifications of these functions are similar to those of strfromd, strfromf, and strfromld (7.22.1.2a) as defined in Part 1 (10.2) of Technical Specification 18661. These functions are declared in <stdlib.h>.

35

© ISO/IEC 2013 – All rights reserved

Change to C11 + TS18661-1:

After 7.22.1.2a, add:

7.22.1.2b The strfromd/ functions

Synopsis

5 [1] #define __STDC_WANT_IEC_60559_DFP_EXT___ #include <stdlib.h> int strfromd32(char * restrict s, size_t n, const char * restrict format, _Decimal32 fp); int strfromd64(char * restrict s, size_t n, const char * restrict format, _Decimal64 fp); int strfromd128(char * restrict s, size_t n, const char * restrict format, _Decimal128 fp);

Description

15 [2] The strfromdN functions are equivalent to snprintf(s, n, format, fp) (7.21.6.5), except the format string contains only the character %, an optional precision that does not contain an asterisk *, and one of the conversion specifiers a, A, e, E, f, F, g, or G, which applies to the type (_Decimal32, _Decimal64, or _Decimal128) indicated by the function suffix (rather than by a length modifier). Use of these functions with any other format string results in undefined behavior.

20 Returns

[3] The strfromdN functions return the number of characters that would have been written had n been sufficiently large, not counting the terminating null character. Thus, the null-terminated output has been completely written if and only if the returned value is less than n.

12.9 Type-generic math for decimal in <tgmath.h>

25 The following changes to C11 + TS18661-1 enhance the specification of type-generic macros in <tgmath.h> to apply to decimal floating types, as well as standard floating types.

Changes to C11 + TS18661-1:

In 7.25, replace paragraphs 2 and 3:

- [2] Of the <math.h> and <complex.h> functions without an f (float) or l (long double) suffix,
 several have one or more parameters whose corresponding real type is double. For each such function, except modf, setpayload, and setpayloadsig, there is a corresponding *type-generic macro*.313) The parameters whose corresponding real type is double in the function synopsis are generic parameters. Use of the macro invokes a function whose corresponding real type and type domain are determined by the arguments for the generic parameters.314)
- 35 [3] Except for the macros for functions that round result to a narrower type (7.12.13a), use of the macro invokes a function whose generic parameters have the corresponding real type determined as follows:
 - First, if any argument for generic parameters has type long double, the type determined is long double.
- 40 Otherwise, if any argument for generic parameters has type double or is of integer type, the type determined is double.
 - Otherwise, the type determined is float.

with:

5

10

15

30

[2] This clause specifies a many-to-one correspondence of functions in <math.h> and <complex.h> with type-generic macros.313) Use of a type-generic macro invokes a corresponding function whose type is determined by the types of the arguments for particular parameters called the generic parameters.314)

[3] Of the <math.h> and <complex.h> functions without an f (float) or l (long double) suffix, several have one or more parameters whose corresponding real type is double. For each such function, except modf, setpayload, and setpayloadsig, there is a corresponding type-generic macro.313) The parameters whose corresponding real type is double in the function synopsis are generic parameters.

[3a] Some of the <math.h> functions for decimal floating types have no unsuffixed counterpart. Of these functions with a d64 suffix, some have one or more parameters whose type is _Decimal64. For each such function, except decodedecd64, encodedecd64, decodebind64, and encodebind64, there is a corresponding type-generic macro. The parameters whose real type is Decimal64 in the function synopsis are generic parameters.

[3b] If arguments for generic parameters of a type-generic macro are such that some argument has a corresponding real type that is of standard floating type and another argument is of decimal floating type, the behavior is undefined.

- [3c] Except for the macros for functions that round result to a narrower type (7.12.13a), use of a type generic macro invokes a function whose generic parameters have the corresponding real type determined by the corresponding real types of the arguments as follows:
 - First, if any argument for generic parameters has type _Decimal128, the type determined is Decimal128.
- Otherwise, if any argument for generic parameters has type _Decimal64, or if any argument for generic parameters is of integer type and another argument for generic parameters has type _Decimal32, the type determined is _Decimal64.
 - Otherwise, if any argument for generic parameters has type _Decimal32, the type determined is _Decimal32.
 - Otherwise, if the corresponding real type of any argument for generic parameters is long double, the type determined is long double.
 - Otherwise, if the corresponding real type of any argument for generic parameters is double or is of integer type, the type determined is double.
 - Otherwise, if any argument for generic parameters is of integer type, the type determined is double.
- 35 Otherwise, the type determined is float.

If neither <math.h> nor <complex.h> define a function whose generic parameters have the determined corresponding real type, the behavior is undefined.

In 7.25#5, replace the last sentence:

If all arguments for generic parameters are real, then use of the macro invokes a real function;otherwise, use of the macro results in undefined behavior.

with:

If all arguments for generic parameters are real, then use of the macro invokes a real function (provided <math.h> defines a function of the determined type); otherwise, use of the macro results in undefined behavior.

5 In 7.25#6, replace the last sentence:

Use of the macro with any real or complex argument invokes a complex function.

with:

Use of the macro with any argument of standard floating or complex type invokes a complex function. Use of the macro with an argument of decimal floating type results in undefined behavior.

10 Change 7.25.6a from:

[7.25.6a] The functions that round result to a narrower type have type-generic macros whose names are obtained by omitting any f or 1 suffix from the function names. Thus, the macros are:

	fadd	fmul	ffma
	dadd	dmul	dfma
5	fsub	fdiv	fsqrt
	dsub	ddiv	dsqrt

All arguments are generic. If any argument is not real, use of the macro results in undefined behavior. If any argument has type long double, or if the macro prefix is d, the function invoked has the name of the macro with an l suffix. Otherwise, the function invoked has the name of the macro (with no suffix).

to:

15

20

[7.25.6a] The functions that round result to a narrower type have type-generic macros whose names are obtained by omitting any suffix from the function names. Thus, the macros with f or d prefix are:

25	fadd	fmul	ffma
	dadd	dmul	dfma
	fsub	fdiv	fsqrt
	dsub	ddiv	dsqrt

30 and the macros with d32 or d64 prefix are:

d32add	d32mul	d32fma
d64add	d64mul	d64fma
d32sub	d32div	d32sqrt
d64sub	d64div	d64sqrt

35

All arguments are generic. If any argument is not real, use of the macro results in undefined behavior. If the macro prefix is \pm or d, use of an argument of decimal floating type results in undefined behavior. If the macro prefix is d32 or d64, use of an argument of standard floating type results in undefined behavior. The function invoked is determined as follows:

- If any argument has type _Decimal128, or if the macro prefix is d64, the function invoked has the name of the macro, with a d128 suffix.
 - Otherwise, if the macro prefix is d32, the function invoked has the name of the macro, with a d64 suffix.

- Otherwise, if any argument has type long double, or if the macro prefix is d, the function invoked has the name of the macro, with an 1 suffix.
- Otherwise, the function invoked has the name of the macro (with no suffix).

After 7.25#6a, before 7.25#6b (see Part 1 of Technical Specification 18661), add the paragraph:

5 [6a+] For each d64-suffixed function in <math.h>, except decodedecd64, encodedecd64, decodebind64, and encodebind64, that does not have an unsuffixed counterpart, the corresponding type-generic macro has the name of the function, but without the suffix. These type-generic macros are:

	<math.h></math.h>	type-generic
10	function	macro
	quantized N	quantize
	${\tt samequantumd} N$	samequantum
	quantumdN	quantum
15	llquantexpdN	llquantexp

Use of the macro with an argument of standard floating or complex type or with only integer type arguments results in undefined behavior.

After 7.25#6b, add the paragraph:

20 [6c] A type-generic macro cbrt that supports decimal floating-point functions and that is affected by constant rounding modes as specified in Part 1 of Technical Specification 18661 could be implemented as follows:

	#ifdef STDC WANT I	EC 60559 DFP EXT	
	<pre>#define cbrt(X)</pre>	Generic((X),	\
25		 Decimal128: cbrtd128(X),	\
		<pre>Decimal64: cbrtd64(X),</pre>	\
		<pre>Decimal32: cbrtd32(X),</pre>	\
		long double: cbrtl(X),	\
		<pre>default: _Roundwise_cbrt(X) ,</pre>	\
30		float: cbrtf(X)	\
)	
	#else		
	<pre>#define cbrt(X)</pre>	_Generic((X),	\
		long double: cbrtl(X),	\
35		<pre>default: _Roundwise_cbrt(X) ,</pre>	\
		float: cbrtf(X)	\
)	
	#endif		

40 where <u>Roundwise_cbrt()</u> is equivalent to cbrt() invoked without macro-replacement suppression.

In 7.25#7, insert at the beginning of the example:

```
#define STDC WANT IEC 60559 DFP EXT
```

In 7.25#7, append to the declarations:

```
#if __STDC_IEC_60559_DFP__ >= 201ymmL
    _Decimal32 d32;
    _Decimal64 d64;
5     _Decimal128 d128;
#endif
```

In 7.25#7, append to the table:

10	exp(d64)	expd64 (d64)
10	sqrt(d32)	sqrtd32(d32)
	fmax(d64, d128)	fmaxd128(d64, d128)
	pow(d32, n)	powd64(d32, n)
	remainder(d64, d)	undefined behavior
	creal(d64)	undefined behavior
15	remquo(d32, d32, &n)) undefined behavior
	llquantexp(d)	undefined behavior
	quantize(dc)	undefined behavior
	<pre>samequantum(n, n)</pre>	undefined behavior
	d32sub(d32, d128)	d32subd128(d32, d128)
20	d32div(d64, n)	d32divd64(d64, n)
	d64fma(d32, d64, d12	28) d64fmad128(d32, d64, d128)
	d64add(d32, d32)	d64addd128(d32, d32)
	d64sqrt(d)	undefined behavior
	dadd(n, d64)	undefined behavior

Bibliography

- [1] ISO/IEC 9899:2011, Information technology Programming languages, their environments and system software interfaces Programming Language C
- [2] ISO/IEC 9899:2011/Cor.1:2012, Technical Corrigendum 1
- 5 [3] ISO/IEC/IEEE 60559:2011, Information technology Microprocessor Systems Floating-point arithmetic
 - [4] ISO/IEC TR 24732:2009, Information technology Programming languages, their environments and system software interfaces Extension for the programming language C to support decimal floating-point arithmetic
- 10 [5] IEC 60559:1989, Binary floating-point arithmetic for microprocessor systems, second edition
 - [6] IEEE 754-2008, IEEE Standard for Floating-Point Arithmetic
 - [7] IEEE 754–1985, IEEE Standard for Binary Floating-Point Arithmetic
 - [8] IEEE 854–1987, IEEE Standard for Radix-Independent Floating-Point Arithmetic